YelloBox-Solar Home System

K088T232XYG

Brand name: Solar Run

Results based on test procedures detailed in IEC TS 62257-9-5:2024

Verify online:

https://data.verasol.org/products/sek/ssr-k088t2

December 31, 2026



Meets the Requirements in IEC TS 62257-9-8:2025 for Size B kits

Mobile charging

Pay-As-You-Go option available

Light point(s)



Plug-and-play



WARRANTY INFORMATION

A 2-year warranty covering manufacturing defects in the system and a 1-year warranty for the radio.

PERFORMANCE DETAILS

Run time after a typical day of solar charging
(assuming Ek/Mh/m²/day)

(assuming 5kWh/m²/day)

VeraSol Certified?	Included in kit?	Annliance" Description		Used alone ^b	Used in combination ^c
yes	included	Main lighting unit	4 light points on high totaling 830 lumens and 5 W power	6.6 hours	3 hours
yes	included	Torch	56 lm torch (LiFePO4 battery: 0.4 Ah, 3.2 V)	12 hours	3 hours
yes	included	Radio	Portable radio (Li-ion battery: 1.9 Ah, 3.7 V), with a power consumption of 0.44 W while in use	98 hours	2.3 hours
no	not included	Smart phone	Smart phone (15 Wh battery)	2 full charge(s)	0.77 full charge(s)

Available daily electrical energy [Wh/day]	34
--	----

Performance measure	Brightness setting: Three lights on "high", one integrated light on high, and one torch on "torch"
Lighting full battery run time for main unit [hours]	6.6
Lighting full battery run time of the Torch powered by Torch battery (hours)	2.5
Total lighting service (lumen-hours/solar-day) (includes the both main lighting unit and any lights with internal batteries included with the product)	6020

^a Only included appliances were tested. Run times and power ratings for appliances sold separately come from manufacturer ratings or standard estimates.

^b Without any other loads used during the run time

^c Based on an example use profile with all of the appliances listed in the "Used in combination" column used simultaneously.

^d Lighting full battery run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

LIGHTING DETAILS									
Lamp name	Number of lamps	Number of settings	Setting name	Light output [lm]	Power Consumption [W]	Lumen efficacy ^e [lm/W]	CRI ^f	CCTg	Lumen maintenance ^h
2 W lamp	3	2	high	250	1.4	170	80	6390	98
Integrated light	1	3	high	77	0.79	98	74	7490	97
Torch	1	2	torch	56	0.61	92	72	7450	98

^e Lumen efficacy is the power consumption at a light point during the light output test.

^f Color Rendering Index. An index of 100 is equivalent to viewing objects in daylight; above 80 is considered good.

^g Correlated Color Temperature in kelvin. Describes color appearance as warm (2700-3000 K), cool (3000-5000 K), or daylight (>5000 K).

^h Percent of the original light output that remains after 2,000 hours of run time.

PORTS							
2	USB 2.0 type A	-	Mobile phones, torches, and radios can be charged. Adapters are included.				
5	Barrel jack		12 V ports available to power light points.				
DURABILI	TY						
Overall o	durability and workmanship		Pass				
Durabilit	ry tests passed		Switch test, Drop test, Strain relief test, Physical ingress protection, PV durability tests				
Main		Main Unit	Water ingress protection not tested, meant for indoor use only.				
		PV module	Has protection from permanent outdoor exposure				
Level of	water protection	Torch	Has protection from frequent rain; met IPX3				
		Radio	Has protection from frequent rain; met with appropriate warning label				
		2 W bulb	Water ingress protection not tested, meant for indoor use only.				
SOLAR DE	ETAILS						
PV Mode	ule Type		Monocrystalline silicon				
PV Maxi	imum Power		12 W				
PV Rate	ed Power		12 W				
PV Oper	n-Circuit Voltage (V _{OC})		12.5 V				
MAIN UNIT	BATTERY DETAILS						
Battery F	Replaceability		Easily replaceable with common tools; however, the warranty is void if product is opened.				
Battery (Chemistry		Lithium iron phosphate				
Battery F	Package Type		32700				
Battery (Capacity (tested)		6 Ah				
Battery (Capacity (rated)		6 Ah				
Battery I	Nominal Voltage		6.4 V				
Battery s	status / other indicator lights		One LED indicator for battery life.				
PRODUCT	DETAILS						
Compan	ny Name (full)		Shenzhen Solar Run Energy Co., Ltd				
Compan	ny Name ("brand")		Solar Run				
Product Name			YelloBox-Solar Home System				
Product Model or ID Number			K088T232XYG				
Company Contact Information			eng@solarunoffgrid.com				
Company Website			www.solarunoffgrid.com				
Mass			n/a				
SSS INFO	RMATION						
Expiration	on Date		December 31, 2026				
Revision	1		2025.09				