S50 StarTimes Software Technology Co., Ltd



Meets the Requirements in IEC TS 62257-9-8:2020 for Size A kits



Mobile charging



Pay-As-You-Go option available

sults based on test procedures detailed in IEC TS 62257-9-5 and IEC TS 62257-9-



Light point(s)



Plug-and-play



PERFORMANCE DETAILS

A 2-year warranty for the main unit with the battery and integrated radio, and the included LED bulbs; a 1-year warranty for the included USB charging cables (optional); and a 5-year warranty for the PV module.

				chai	ypical day of solar rging kWh/m²/day)
VeraSol Certified?	Included in Kit?	Appliance ^a	Description	Used alone ^b	Used in combination ^c
yes	included	Main lighting unit	3 light points on high totaling 350 lumens and 3 W	8.7 hours	0.61 hours
yes	included	Radio	integrated battery with a power consumption of 0.52W while in-use	47 hours	0.48 hours
no	not included	Tablet	Tablet Computer (15Wh battery)	1.2 hours	
no	not included	Fan	Small table fan (16" or smaller diameter, 10 W power)	0.9 hours	0.8 hours
no	not included	Mobile phone	Smart phone (5.7 Wh battery)	3.3 full charge(s)	0.17 full charge(s)

Available daily algebraed property (AAIIA)	26
Available daily electrical energy (Wh/day)	26

Performance measure	Brightness setting: On
Lighting full battery run time ^d for main unit (hours)	11
Total lighting service (lumen-hours/solar-day) (includes the both main lighting unit and any lights with internal batteries included with the product)	3050

a Only included appliances were tested. Run times and power ratings for appliances sold separately come from manufacturer ratings or standard estimates.

d Lighting full battery run time estimates do not account for mobile phone charging or other auxiliary loads; the run time is defined as the time until the output is 70% of the initial, stabilized output.

1	LIGHTING DETAILS	i								
-	Lamp name	Number of lamps	Number of settings	Setting	Light output (lm)	Lumen efficacy ^e (lm/W)	CRI ^f	CCT ^g	Distribution type	Lumen maintenance ^h
	Hanging Lamp	3	1	On	120	120	87	5700	Wide	100%

^e Lumen efficacy is the power consumption at a light point during the light output test.

^b Without any other loads used during the run time

^c Based on an example use profile with all of the appliances listed in the "Used in combination" column used simultaneously.

^f Color Rendering Index. An index of 100 is equivalent to viewing objects in daylight; above 80 is considered good.

⁹ Correlated Color Temperature in degrees Kelvin. Describes color appearance as warm (2700-3000 K), cool (3000-5000 K), or daylight (>5000 K)

^h Percent of the original light output that remains after 2,000 hours of run time

PORTS			
2	USB 2.0 type A		Mobile phones and tablets can be charged, USB-compatible fans may be powered, and one of the USB ports can play media. Adapters are optional.
3	Barrel jack	-	9.6 V ports available to power light points.

Overall durability and workmanship Durability tests passed		Pass Switch test, Drop test, Strain relief test, Physical ingress protection, PV durability tests		
Level of water protection	PV module			
	Hanging Lamp	Water ingress protection not tested, meant for indoor use only.		
SOLAR DETAILS				
PV module type		Monocrystalline silicon		
PV maximum power		10 watts		
MAIN UNIT BATTERY DETAILS				
Battery replaceability		Easily replaceable with common tools; however, the warranty is void if product is opened.		
Battery chemistry		Lithium iron phosphate		
Specific Li-ion battery chemistry		lithium iron phosphate		
Battery package type		3x 26700		
Battery capacity		4.1 Ah		
Battery nominal voltage		9.6 V		
Battery status/ other indicator lights		One battery status indicator that shows battery charge level.		
PRODUCT DETAILS				
Manufacturer name		StarTimes Software Technology Co., Ltd		
Product name		Solar Power System		
Product model / ID number		S50		
Contact information		wangliang@startimes.com.cn		
Website		www.startimes.com.cn		
Dimensions (entire product in package)		34.3 x 25.2 x 12.3 cm		
Mass		2740 g		
SS INFORMATION				
Specs sheet expiration date		August 31, 2025		
Revision		2024.03		