VeraSol Standardized Specifications Book

Manufacturer: Omnivoltaic Energy Solutions Co., Ltd

Component Family Name: LUMNS Family

Date of Standardized November 30, 2022 Specifications Book Expiration:

Verify Online: https://data.verasol.org/products/sek/omni-lumnfamily

Contact Information: marketing@omnivoltaic.com

Website: www.omnivoltaic.com



This VeraSol Standardized Specifications Book presents a component-level Standardized Specifications Sheet listing the available components in the product family by component type, each individual component's performance rating, and performance results for each component tested according to the Edition 4 of IEC 62257-9-5. Following the component-level Standardized Specifications Sheet is a list of the systems covered by this Specifications Book that use combinations of these components.

NOTICE: Systems or kits developed using components from the component family will each perform differently and have not all been evaluated on a system-level basis. All systems listed in this Specifications Book are regarded to have passed the applicable Lighting Global Quality Standards.

Quality Standards Framework Version: 2021

Revision: 2021.02

Component-Level Standardized Specifications Sheet

Omnivoltaic Energy Solutions Co., Ltd LUMNS Family

| Battery / Control Box | | | | | | | | |
|------------------------|------------------------|------------------------|---------------------------------------|---|--|--|--|--|
| Name / Model Number | Battery Chemistry | Nominal Voltage (V) | Battery Capacity Rating (Ah) | Measured Battery Capacity (Ah) | | | | |
| 2500 mAh battery | Lithium iron phosphate | 7.2 | 2.6 | 2.5 | | | | |
| 5000 mAh battery | Lithium iron phosphate | 7.2 | 5.2 | 5.0 | | | | |
| Torch Battery | Lithium iron phosphate | 3.2 | 0.5 | 0.5 | | | | |

| PV Module | | |
|---------------------|------------------------------|----------------------------|
| Name / Model Number | Peak Power at STC Rating (W) | Measured Peak Power at STC |
| 4.9 W PV Module | 4 | 4.9 |
| 5.7 W PV Module | 6 | 5.7 |
| 12 W PV Module | 12 | 12 |

| Light Sources* | | | | | | | | | |
|-----------------------|----------------------|--------|-------|-------|---------|-------|-------|----------|-------|
| | Luminous Flux Rating | | | | | | = | | |
| | | (lm) | | F | lux (lm | 1) | Eff | icacy (I | m/W) |
| Name / Model Number | Super | Normal | Night | Super | Normal | Night | Super | Normal | Night |
| Main Lamp 200 lm | 200 | | 25 | 210 | | 21 | 160 | | 110 |
| Main Lamp 300 lm | 300 | | 25 | 320 | | 25 | 160 | | 130 |
| Main Lamp 500 lm | 500 | | 51 | 500 | | 51 | 150 | | 140 |
| Secondary Lamp 100 lm | 100 | | 25 | 110 | | 25 | 160 | | 160 |
| Torch (front light) | | 33 | | | 39 | | | 120 | |

| Appliances" | | | | | | |
|---------------------------------|---|-----------------------|--|--------------------------------------|---|--|
| Name / Model Number | Description | Rated Power (W) | Measured Power During Use (W) | Rated Battery Capacity (Ah) | Measured Battery Capacity (Ah) | |
| Solar Powered Radio (RD/SPRD-A) | portable radio with internal battery, charges via USB | 3 | 0.39* | 1 | 1 | |

^{*}The power test is conducted according to IEC 62087-6:2015 (test procedure) and IEC 62087-1:2015 (test equipment requirement)

NOTICE: As indicated, not all components listed on this page were tested according to the Quality Test Method (QTM) in Edition 4 of IEC 62257-9-5. However, based on the satisfactory performance of the tested components in the family, the components that were not tested are regarded to have passed the applicable Lighting Global Quality Standards. In addition, all tested components passed an internal inspection, the full array of applicable QTM durability tests, as well as ingress protection testing (where applicable).

*Light points and appliances may perform differently when used with different systems.

List of Covered Systems

Omnivoltaic Energy Solutions Co., Ltd LUMNS Family

| System Name | Main Lamp 500 lm 5000 mAh battery | Main Lamp 320 lm 5000 mAh battery | Main Lamp 300 lm 2500 mAh battery | Main Lamp 200 lm 2500 mAh battery | Secondary Lamp 110 lm | 4.9 W PV Module | 5.7 W PV Module | 12 W PV Module | Torch | Keypad | Radio |
|---------------|--|--|--|--|-----------------------------|--------------------|--------------------|-------------------|-------|--------|-------|
| L300 | | | 1 | | | 1 | | | | | |
| L300_KEYP | | | 1 | | | 1 | | | | 1 | |
| L300X_KEYP_RD | | | 1 | | | 1 | | | 1 | 1 | 1 |
| L500 | 1 | | | | | | 1 | | | | |
| L500_KEYP** | 1 | | | | | | 1 | | | 1 | |
| L500X_KEYP_RD | 1 | | | | | | 1 | | 1 | 1 | 1 |
| M300 | | | | 1 | 1 | | 1 | | | | |
| M300X | | | | 1 | 1 | | 1 | | 1 | | |
| M300_KEYP | | | | 1 | 1 | | 1 | | | 1 | |
| M300X_KEYP | | | | 1 | 1 | | 1 | | 1 | 1 | |
| M300X_KEYP_RD | | | | 1 | 1 | | 1 | | 1 | 1 | 1 |
| M400 | | | | 1 | 2 | | 1 | | | | |
| M400X | | | | 1 | 2 | | 1 | | 1 | | |
| M400_KEYP | | | | 1 | 2 | | 1 | | | 1 | |
| M400X_KEYP | | | | 1 | 2 | | 1 | | 1 | 1 | |
| M400X_KEYP_RD | | | | 1 | 2 | | 1 | | 1 | 1 | 1 |
| M500 | | 1 | | | 2 | | | 1 | | | |
| M500X | | 1 | | | 2 | | | 1 | 1 | | |
| M500_KEYP | | 1 | | | 2 | | | 1 | | 1 | |
| M500X_KEYP | | 1 | | | 2 | | | 1 | 1 | 1 | |
| M500X_KEYP_RD | | 1 | | | 2 | | | 1 | 1 | 1 | 1 |
| M600 | | 1 | | | 3 | | | 1 | | | |
| M600X | | 1 | | | 3 | | | 1 | 1 | | |
| M600_KEYP** | | 1 | | | 3 | | | 1 | | 1 | |

| M600X_KEYP | 1 | | 3 | | 1 | 1 | 1 | |
|---------------|---|---|---|--|---|---|---|---|
| M600X_RD | 1 | | 3 | | 1 | 1 | | 1 |
| M600X_KEYP_RD | 1 | | 3 | | 1 | 1 | 1 | 1 |
| M630 | | 3 | | | 1 | | | |
| M630X | | 3 | | | 1 | 1 | | |
| M630_KEYP | | 3 | | | 1 | | 1 | |
| M630X_KEYP | | 3 | | | 1 | 1 | 1 | |
| M630X_KEYP_RD | | 3 | | | 1 | 1 | 1 | 1 |
| M700 | 1 | | 4 | | 1 | | | |
| M700X | 1 | | 4 | | 1 | 1 | | |
| M700_KEYP | 1 | | 4 | | 1 | | 1 | |
| M700X_KEYP | 1 | | 4 | | 1 | 1 | 1 | |
| M700X_KEYP_RD | 1 | | 4 | | 1 | 1 | 1 | 1 |

Only the M600_KEYP was fully tested as a system according to Edition 4 of IEC 62257-9-5. Individual Standardized Specifications Sheets (SSS) that report system-level performance are available for the M600_KEYP at https://data.verasol.org Systems that were not tested, but that were developed using components from the component family will perform differently than the system(s) shown in the individual system-level SSS. All systems listed above are regarded to have passed the applicable Lighting Global Quality Standards.

Unless otherwise noted, the following information applies to all listed systems and components:

Warranty Information

Two year warranty on all kits and components. Radio has a 1 year warranty

| | Marks and Certifications | |
|-----------------------|--------------------------|--|
| Factory certification | ISO 9001:2008 | |

Available Daily Electrical Energy

Omnivoltaic Energy Solutions Co., Ltd LUMNS Family

| s | ystem Name | Available Daily Electrical Energy (Wh/day) |
|--------|------------|--|
| L500** | | 21 |
| M600** | | 35 |

^{**}Tested as full systems. Individual SSS available on VeraSol website.

NOTICE:

The available daily electrical energy (Wh/day) is calculated for fully tested systems following the energy service calculations as described in IEC/TS 62257-9-5 Ed. 4. For products in a family that are not tested as a full system, estimations of available daily electrical energy (Wh/day) are calculated according to an alternative method using data from the test reports of fully-tested products and components.