

Bend 90°

KS90 K-600 R=300 XPG


Bends KS90 are used to make 90° angles for KS20 - and KS60-type cable ladders when the bending radius of cables or other needs require this. KS90 bends' inside radius options are R=300 mm.

Bends can be connected to cable ladders by using joints SSR or SSU.



Product name	KS90 K-600 R=300 XPG		
SKU	1431053		
Material	Steel		
Corrosivity category	C1-C4		
Color	Grey		
Sales unit	PCE		
Packing size	10 PCE		
Dimensions (mm) Width Height Length	1100	60	1100
Weight (kg/pce)	3,9		
GTIN	6438377161637		
Surface finish	Manufactured of coated steel in accordance with standard EN 10346		

Dimension A (mm)	600
Dimension B (mm)	1100
Radius R (mm)	300
CO2e/kg	2,72



Series / Product	A	B	R
KS90 K-200 R=300	200	700	300
KS90 K-300 R=300	300	800	300
KS90 K-400 R=300	400	900	300
KS90 K-500 R=300	500	1000	300
KS90 K-600 R=300	600	1100	300
KS90 K-200 R=400	200	900	400
KS90 K-300 R=400	300	1000	400
KS90 K-400 R=400	400	1100	400
KS90 K-500 R=400	500	1200	400
KS90 K-600 R=400	600	1300	400