Corner piece
KS100 L90-400 R=300 PG

Bends KS100 L90 are used to make 90° angles for KS100-type cable ladders when the bending radius of cables or other needs require this. KS100 L90 inside radius is R=300 mm.

Bends can be connected to cable ladders by using joints KS100 J.





Tuote / Product	A	B	R
KS100 L-200 R=300	200	700	300
KS100 L-300 R=300	300	800	300
KS100 L-400 R=300	400	900	300
KS100 L-500 R=300	500	1000	300
KS100 L-600 R=300	600	1100	300
KS100 L-200 R=600	200	985	600
KS100 L-300 R=600	300	1085	600
KS100 L-400 R=600	400	1185	600
KS100 L-500 R=600	500	1285	600
KS100 L-600 R=600	600	1385	600

Product name	**KS100 L90-400 R=300 PG**		
SKU	**1478097**		
Material	**Steel**		
Corrosivity category	**C1-C2**		
Color	**Grey**		
Sales unit	**PCE**		
Packing size	**10 PCE**		
Dimensions (mm) Width | Height | Length	**900**	**100**	**900**
Weight (kg/pce)	**5**		
GTIN	**6438377161712**		
Surface finish	**Manufactured of hot-dip galvanized steel in accordance with standard EN 10346**		

Dimension A (mm)	400
Dimension B (mm)	900
Radius R (mm)	300
CO2e/kg	2,61

MEKA PRO OY
Konetie 25 / FI-90620 Oulu, Finland / +358 207 450 800 / meka@meka.eu

© Right to changes reserved. Propria Oy is the owner of all Meka Pro Oy trademarks.