

Safety data sheet according to Regulation (EC) No. 1907/2006

SECTION 1. Identification of the substance/mixture and of the company/undertaking.

1.1. Product identifier.

Code. **HI4015A-00**
Product name. **SAOB Reagent A for Sulfide Electrodes**

1.2. Relevant identified uses of the substance or mixture and uses advised against.

Intended use. **Anti-Oxidant Buffer Solution for Sulfide Standard.**

1.3. Details of the supplier of the safety data sheet.

Name. **Hanna Instruments S.R.L.**
Full address. **str. Hanna Nr 1**
District and Country. **457260 loc. Nusfalau (Salaj) Romania**
Tel. **(+40) 260607700**
Fax. **(+40) 260607700**
e-mail address of the competent person responsible for the Safety Data Sheet. **msds@hanna.ro**

1.4. Emergency telephone number.

For urgent inquiries refer to. **Emergency Number - International: +(1)-703-527-3887 - UK, London: +(44)-870-8200418 - CHEMTREC 24 hours/365 days**

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Substance or mixture corrosive to metals, category 1	H290	May be corrosive to metals.
Specific target organ toxicity - repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Skin corrosion, category 1A	H314	Causes severe skin burns and eye damage.
Serious eye damage, category 1	H318	Causes serious eye damage.

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: **Danger**

Hazard statements:

H290 May be corrosive to metals.
H373 May cause damage to organs through prolonged or repeated exposure.
H314 Causes severe skin burns and eye damage.

Precautionary statements:

P280 Wear protective gloves, protective clothing, eye protection and face protection.

SECTION 2. Hazards identification. ... / >>**P303+P361+P353**
P305+P351+P338

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Collect spillage.
Immediately call a POISON CENTER or doctor.

P391
P310**Contains:**EDTA DISODIUM SALT
SODIUM HYDROXIDE**2.3. Other hazards.**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients.**3.1. Substances.**

Information not relevant.

3.2. Mixtures.**Contains:**

Identification.	x = Conc. %.	Classification 1272/2008 (CLP).
-----------------	--------------	---------------------------------

SODIUM HYDROXIDE

CAS.	1310-73-2	$5 \leq x < 9$	Met. Corr. 1 H290, Skin Corr. 1A H314
EC.	215-185-5		
INDEX.	011-002-00-6		
Reg. no.	01-2119457892-27		

EDTA DISODIUM SALT

CAS.	6381-92-6	$5 \leq x < 9$	Acute Tox. 4 H332, STOT RE 2 H373
EC.	205-358-3		
INDEX.			
Reg. no.	01-2119486775-20		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures.**4.1. Description of first aid measures.**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully.
Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed.

Specific information on symptoms and effects caused by the product are unknown.

For symptoms and effects caused by the contained substances, see chap. 11.

SODIUM HYDROXIDE

Irritation and corrosion, Cough, Shortness of breath, collapse, death. Risk of blindness!.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.**5.1. Extinguishing media.****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

SECTION 5. Firefighting measures. ... / >>

UNSUITABLE EXTINGUISHING EQUIPMENT
None in particular.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE
Do not breathe combustion products.

EDTA DISODIUM SALT

Combustible. Development of hazardous combustion gases or vapours possible in the event of fire. Fire may cause evolution of: nitrogen oxides.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed.

Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:

ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits
HUN	Magyarország	50/2011. (XII. 22.) NGM rendelet a munkahelyek kémiai biztonságáról
ROU	România	Monitorul Oficial al României 44; 2012-01-19

SECTION 8. Exposure controls/personal protection. ... / >>

TLV-ACGIH ACGIH 2016

SODIUM HYDROXIDE

Threshold Limit Value.

Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm
VLA	ESP			2	
VLEP	FRA	2			
WEL	GBR			2	
AK	HUN	2		2	
TLV	ROU	1		3	
TLV-ACGIH				2 (C)	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers.				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation.			VND	1 mg/m3			VND	1 mg/m3

EDTA DISODIUM SALT

Predicted no-effect concentration - PNEC.

Normal value in fresh water	2,2	mg/l
Normal value in marine water	0,22	mg/l
Normal value of STP microorganisms	43	mg/l
Normal value for the terrestrial compartment	0,72	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers.				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral.	VND	25 mg/kg/d						
Inhalation.	1,2 mg/m3	VND	0,6 mg/m3	VND	3 mg/m3	VND	1,5 mg/m3	VND

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

SODIUM HYDROXIDE

Methods for measurement of the workplace atmosphere have to correspond to the requirements of norm OSHA ID-121.

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

SECTION 8. Exposure controls/personal protection. ... / >>

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance	liquid
Colour	colourless
Odour	odourless
Odour threshold.	Not available.
pH.	> 13
Melting point / freezing point.	Not available.
Initial boiling point.	Not available.
Boiling range.	Not available.
Flash point.	> 60 °C.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	1,100
Solubility	soluble in water
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.

9.2. Other information.

Total solids (250°C / 482°F)	14,35 %
VOC (Directive 2010/75/EC) :	0
VOC (volatile carbon) :	0

SECTION 10. Stability and reactivity.

10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

SODIUM HYDROXIDE
Hygroscopic.

10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

SODIUM HYDROXIDE

Risk of explosion/exothermic reaction with: Acetone, Nitriles, phosphides, halogens, halogen-halogen compounds, chlorinated solvents, Ethylene oxide, Hydrazine hydrate, hydroxylamine, anhydrides, Peroxides, Acrolein, Acid chlorides, Acids, sulphuric acid, silver salt, hydrogen peroxide, organic nitro compounds, Water, Metals, Light metals. Possible formation of: Hydrogen. Violent reactions possible with: ammonium compounds, organic combustible substances, phenols. Generates dangerous gases or fumes in contact with: persulfates, Sodium borohydride, Oxides of phosphorus.

EDTA DISODIUM SALT

Violent reactions possible with: Strong oxidizing agents.

SECTION 10. Stability and reactivity. ... / >>

10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

SODIUM HYDROXIDE

Exposure to the air, moisture and sources of heat.

EDTA DISODIUM SALT

Strong heating.

10.5. Incompatible materials.

SODIUM HYDROXIDE

Strong acids, ammonia, zinc, lead, aluminium, water and flammable liquids.

EDTA DISODIUM SALT

Aluminium, Copper, Copper alloys, Nickel, Zinc.

10.6. Hazardous decomposition products.

Information not available.

SECTION 11. Toxicological information.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects.

EDTA DISODIUM SALT

Skin irritation, Rabbit, Result: No irritation, (anhydrous substance) - Eye irritation, Rabbit, Result: No eye irritation, (anhydrous substance) - Sensitisation, Sensitisation possible in predisposed persons - Germ cell mutagenicity Genotoxicity in vitro, Ames test, Salmonella typhimurium, Result: negative (anhydrous substance), Mouse lymphoma test, Result: negative, (anhydrous substance) - Specific target organ toxicity, repeated exposure, Target Organs: Respiratory Tract, May cause amage to organs through prolonged or repeated exposure - Repeated dose toxicity, Rat male, Inhalation aerosol, 5 d daily, LOAEL: 0,03 mg/l, Target Organs: Lungs, larynx - Repeated dose toxicity, Rat male and female, Inhalation dust/mist, 90 d daily, NOAEL: 0,003 mg/l, Target Organs: larynx.

SODIUM HYDROXIDE

Acute oral toxicity, Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach - Acute inhalation toxicity, Symptoms: burns of mucous membranes, Cough, Shortness of breath, Possible damages:, damage of respiratory tract - Skin irritation, Rabbit, Result: Causes severe burns - Eye irritation, Rabbit, Result: Irreversible effects on the eye, Causes serious eye damage. Risk of blindness! - Sensitisation, Patch test: human, Result: Does not cause skin sensitisation - Germ cell mutagenicity, Genotoxicity in vitro, Mutagenicity (mammal cell test): micronucleus, Result: negative, (Lit.) Ames test, Result: negative.

ACUTE TOXICITY.

LC50 (Inhalation - vapours) of the mixture:

Not classified (no significant component).

LC50 (Inhalation - mists / powders) of the mixture:

16,667 mg/l

LD50 (Oral) of the mixture:

Not classified (no significant component).

LD50 (Dermal) of the mixture:

Not classified (no significant component).

EDTA DISODIUM SALT

LD50 (Oral).

> 2800 mg/kg Rat

SODIUM HYDROXIDE

LD50 (Oral).

1350 mg/kg Rat

LD50 (Dermal).

1350 mg/kg Rat

SKIN CORROSION / IRRITATION.

Corrosive for the skin.

SERIOUS EYE DAMAGE / IRRITATION.

Causes serious eye damage.

RESPIRATORY OR SKIN SENSITISATION.

SECTION 11. Toxicological information. ... / >>

Does not meet the classification criteria for this hazard class.

GERM CELL MUTAGENICITY.

Does not meet the classification criteria for this hazard class.

CARCINOGENICITY.

Does not meet the classification criteria for this hazard class.

REPRODUCTIVE TOXICITY.

Does not meet the classification criteria for this hazard class.

STOT - SINGLE EXPOSURE.

Does not meet the classification criteria for this hazard class.

STOT - REPEATED EXPOSURE.

May cause damage to organs.

ASPIRATION HAZARD.

Does not meet the classification criteria for this hazard class.

SECTION 12. Ecological information.

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity.**EDTA DISODIUM SALT**

Toxicity to bacteria, EC50 activated sludge: 403 mg/l, 3 h - EC50 *Pseudomonas putida*: 56 mg/l, 8 h (anhydrous substance).

EDTA DISODIUM SALT

LC50 - for Fish. 320 mg/l/96h *Poecilia Reticulata*

SODIUM HYDROXIDE

LC50 - for Fish. 45,4 mg/l/96h *Oncorhynchus mykiss*

EC50 - for Crustacea. 40,38 mg/l/48h *Daphnia*

12.2. Persistence and degradability.**EDTA DISODIUM SALT**

Solubility in water. 20°C mg/l

SODIUM HYDROXIDE

Solubility in water. > 10000 mg/l

Biodegradability: Information not available.

12.3. Bioaccumulative potential.

Information not available.

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.**EDTA DISODIUM SALT**

Discharge into the environment must be avoided.

SODIUM HYDROXIDE

Harmful effect due to pH shift. Forms corrosive mixtures with water even if diluted. Neutralisation possible in waste water treatment plants. Discharge into the environment must be avoided.

SECTION 13. Disposal considerations.

13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

14.1. UN number.

ADR / RID, IMDG, IATA: 1824

14.2. UN proper shipping name.

ADR / RID: SODIUM HYDROXIDE SOLUTION

IMDG: SODIUM HYDROXIDE SOLUTION

IATA: SODIUM HYDROXIDE SOLUTION

14.3. Transport hazard class(es).

ADR / RID: Class: 8 Label: 8



IMDG: Class: 8 Label: 8



IATA: Class: 8 Label: 8



14.4. Packing group.

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards.

ADR / RID: NO

IMDG: NO

IATA: NO

14.6. Special precautions for user.

ADR / RID: HIN - Kemler: 80

Special Provision: -

Limited Quantities: 5 L

Tunnel restriction code: (E)

IMDG: EMS: F-A, S-B

Limited Quantities: 5 L

IATA: Cargo:

Maximum quantity: 60 L

Packaging instructions: 856

Pass.:

Maximum quantity: 5 L

Packaging instructions: 852

Special Instructions:

A3, A803

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso Category - Directive 2012/18/EC: None.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product.

Point. 3

Substances in Candidate List (Art. 59 REACH).

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

WGK 2: Hazard to waters

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Met. Corr. 1	Substance or mixture corrosive to metals, category 1
Acute Tox. 4	Acute toxicity, category 4
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Skin Corr. 1A	Skin corrosion, category 1A
Skin Corr. 1B	Skin corrosion, category 1B
Skin Corr. 1C	Skin corrosion, category 1C
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
H290	May be corrosive to metals.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals

SECTION 16. Other information. ... / >>

- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.