

DILOG



www.dilog.se

Dilog DCT-280HD

- Supporting DVB-C
- SD / HD support (MPEG4 AVC/H.264)
- User friendly Installation
- 1 Cryptoguard Smartcard-Reader
- USB PVR Function (with external HDD)
- Time Shift Mode (with external HDD)
- Event Timer by EPG
- High Definition Video output : HDMI
- S/PDIF Dolby (coaxial) Subtitle support : OSD & VBI insertion for TV
- 4-segment LED Display
- Channel sorting by FTA, CAS, Alphabetic order & Network
- EPG : Now and Next and 7 days EPG
- Variable Input Symbol Rate
- User selectable output resolution
- Multi language OSD
- Fast Channel Change
- Memory for up to 5,000 TV & Radio Channels
- PIG (Picture In Graphic)
- 8 Favorite List & Unlimited Programs per each
- Channel Edit Function
 - Move, Delete, Favorite Edit
 - Parental Lock, Channel Rename, Channel Skip
- Manual PID/ Satellite & TP/ Network Scan
- S/PDIF – coaxial (Digital Audio or Dolby AC3 stream out)
- Software Upgrade via OTC & USB

Technical Specification



A/V Rear Port

HDMI	1 (1.3)
RCA-Jack	Video, Audio L/R Output
Digital Audio (S/PDIF)	Coaxial
USB 2.0	1
RF Modulator	Optional

Front Panel

Display	7-segment, ON/OFF LED
Front Panel Keys	Standby, CH+, CH-
Cardreader	1 Cryptoguard Smartcard Reader

Memory and Chip

CPU	3812
DDR2	128MB
FLASH	8MB

Physical Specification

Net Weight	1,2 kg
Dimensions (WxHxD)	195x40x145 mm
Operating Temperature	0~40°C

Remote Control

Type	Infrared (Carrier Freq. 38kHz)
Qwerty Remote	2 x 1.5 V AAA

Power Supply

Input Voltage	AC100-240V~, 50/60Hz,
---------------	-----------------------

EAN

7 350 021 772 800

DILOG

Dilog Nordic AB
Faktorvägen 9, 434 37 Kungsbacka Sweden

Tel: +46 31 28 88 30
Fax: +46 31 28 82 33
www.dilog.se