

# Server-Grade Encoder E2211, Rev. 5



## Product Overview

Single and Dual Channel Video Encoder. Capable of streaming (1) UHD/4K video, or (2) 1080p60 videos, with up to 16 channels of audio

## Production Audio/Video Input

<b>Connections</b>	(2) 10 bit 6G-SDI & (2) HDMI 2.0a. Input can be either SDI or HDMI, set in software. Only one type of capture interface is enabled at a time (two SDI or two HDMI). Accepts 16 channels of 24-bit 48 kHz embedded audio on video input #1.
<b>Format Types</b>	SD: 525i59.94 NTSC, 625i50 PAL HD: 720p50, 720p59.94, 720p60, 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60, 1080i50, 1080i59.94, 1080i60 UHD: 2160p23.98, 2160p24, 2160p25, 2160p29.97, 2160p30
<b>SDI Compliance</b>	SMPTE 259M, 292M, 424M, ST-2081

## Compression for Streaming

<b>Video Codec</b>	HEVC / H.265 (MPEG-H Part 2), H.264 (MPEG-4 AVC)
<b>Audio Codec</b>	AAC-LC with 1, 2, 5.1, 8, or 16 channels of audio

## General Specifications

<b>Monitor interface</b>	No monitor required. Supplied with a DVI-D emulator (installed).
<b>Network Interface</b>	(2) Gigabit Ethernet LAN
<b>Storage Capacity</b>	256GB SSD (~230 GB available); 150+ TB Written (TBW) Endurance
<b>Misc. Ports</b>	No keyboard or mouse required. (1) PS/2 Mouse/Keyboard Port
<b>Dimensions</b>	Rackmount 2U, 19.0" (W) x 15.5" (D) x 3.5" (H); 21 lbs
<b>Power</b>	100V - 240V Input, 380W maximum draw, redundant hot swappable modules
<b>Warranty</b>	1 Year Limited Manufacturer's Warranty.
<b>Manufactured</b>	U.S.A