

Specification Sheet

Hudson River Collection





PM-2105-B Footprint



PM-2108-B Wavy



PM-2106-B

Gorge

PM-2119-B Pebble

PM-2120-B Meander

PM-2107-B

Stream

PRODUCT DETAILS

Product Type	Rigid Engineered Luxury Vinyl
Collection	Hudson River Collection
Construction	Solid Vinyl Plank
Classification	ASTM F3261-Grade 1, Type A-Smooth, Type B-Embossed
Overall Thickness	4.8mm (0.1890'')
Wear Layer	12mil (0.30mm)
Underlayment	1.5mm IXPE (0.0591'')
Edge Profile	Micro Bevel
Surface Finish	Ceramic Bead
Embossing	Photo Match Embossing
Edge Profile	Easy-to-install with I4F Locking system
Size	7" W x 48" L (180x1220mm)
Square Feet Per Carton	23.64 SQFT/CTN
Pieces Per Carton	10 PIECES/CTN
Weight Per Carton	14.70 KGS/CTN 32.41LBS/CTN
Carton Per Pallet	65 CTNS/PLT
Installation Method	Floating/Glue Down

TECHNICAL PROPERTY

Dimensional Stability	
Curling	
Static Load	
Static Load Limit	
Residual Indentation	
Resistance to Chemicals	
Resistance to Heat	
Resistance to Light	
Critical Radiant Flux	
Smoke Density	
VOCs/TVOCs, Formaldehyde	
Substances of Very High Concern	
Heavy Metals	
Phthalates	
Slip Resistance	
Fungi Resistance	
IIC Rating	
STC Rating	

ASTM F2199 - Passes - ≤0.2% / lineal ft. (305 mm) ISO 23999 - Passes - ≤2mm ASTM F970 - Passes - ≤0.005" (0.13mm) (without underlayer) SIM Test - 1000 psi (0.02mm) (without underlayer) ASTM F1914 - Passes - Average: ≤0.007"(0.18mm) (without underlayer) ASTM F925-Passes -No more than a slight change in surface ASTM F1514 - Passes - Average $\Delta E < 8.0$ ASTM F1515 - Passes - Average $\Delta E < 8.0$ ASTM E648 - Passes - Class I: ≥ 0.45 W/Sq.cm ASTM E662 - Passes - Flaming & Non Flaming≤ 450 CDPH/EHLB Method v1.2 Compliant REACH SVHC 191 - Passes - Per Substance: ≤0.1% w/w ASTM F963 - Passes ASTM D7823 - Passes - CPSC-CH-C1001-09.3 ASTM D2047- Dry:0.38 Wet: 0.90 ASTM G21-15 - Passes ASTM E492 & ASTM E989 - Result: 66 ASTM E90 & ASTM E413 - Result: 68

SUSTAINBILITY

Material Certification Environmental Product Declaration Health Product Declaration

Virgin Vinyl Floor Score® certified **EPD Vinyl Click** HPD 2.1 Vinyl Click - 1000 ppm

SERVICE

Warranties

Limited Lifetime Warranty







