

**Ohio River - Ohio River+ Collection**



PM-2124-B  
Campfire




PM-2123-B  
Earth



PM-2122-B  
Walnut



PM-2126-B  
Middling  
Autumn



PM-2127-B  
Luke Warm



PM-2121-B  
Ice

**PRODUCT DETAILS**

Product Type	<b>Rigid Engineered Luxury Vinyl</b>
Collection	<b>Ohio River and Ohio River+ Collection</b>
Construction	<b>Stone Polymer Composite Tiles</b>
Classification	<b>ASTM F3261-Grade 1, Type A-Smooth, Type B-Embossed</b>
Overall Thickness	<b>5.5mm (0.2165")</b>
Wear Layer	<b>22mil (0.55mm)</b>
Underlayment	<b>1.5mm IXPE (0.0591")</b>
Edge Profile	<b>Painted Bevel</b>
Surface Finish	<b>Ceramic Bead</b>
Embossing	<b>Photo Match Embossing</b>
Edge Profile	<b>Easy-to-install with I4F Locking system</b>
Size	<b>18" W x 36" L (180x1220mm) or (6",12",18" )x36"</b>
Square Feet Per Carton	<b>27.60 SQFT/CTN or 27.64 SQFT/CTN</b>
Pieces Per Carton	<b>6 PIECES /CTN or 9 (3 of each Width)</b>
Weight Per Carton	<b>21.79 KGS/CTN 48 LBS/CTN</b>
Carton Per Pallet	<b>38 CTNS/PLT</b>
Installation Method	<b>Floating/Glue Down</b>

**TECHNICAL PROPERTY**

Dimensional Stability	<b>ASTM F2199 - Passes - <math>\leq 0.2\%</math> / lineal ft. (305 mm)</b>
Curling	<b>ISO 23999 - Passes - <math>\leq 2\text{mm}</math></b>
Static Load	<b>ASTM F970 - Passes - <math>\leq 0.005"</math> (0.13mm) (without underlayer)</b>
Static Load Limit	<b>SIM Test - 1000 psi (0.02mm) (without underlayer)</b>
Residual Indentation	<b>ASTM F1914 - Passes - Average: <math>\leq 0.007"</math> (0.18mm) (without underlayer)</b>
Resistance to Chemicals	<b>ASTM F925-Passes-No more than a slight change in surface</b>
Resistance to Heat	<b>ASTM F1514 - Passes - Average <math>\Delta E &lt; 8.0</math></b>
Resistance to Light	<b>ASTM F1515 - Passes - Average <math>\Delta E &lt; 8.0</math></b>
Critical Radiant Flux	<b>ASTM E648 - Passes - Class I: <math>\geq 0.45 \text{ W/Sq.cm}</math></b>
Smoke Density	<b>ASTM E662 - Passes - Flaming &amp; Non Flaming <math>\leq 450</math></b>
VOCs/TVOCs, Formaldehyde	<b>CDPH/EHLB Method v1.2 Compliant</b>
Substances of Very High Concern	<b>REACH SVHC 191 - Passes - Per Substance: <math>\leq 0.1\% \text{ w/w}</math></b>
Heavy Metals	<b>ASTM F963 - Passes</b>
Phthalates	<b>ASTM D7823 - Passes - CPSC-CH-C1001-09.3</b>
Slip Resistance	<b>ASTM D2047- Dry: 0.38 Wet: 0.90</b>
Fungi Resistance	<b>ASTM G21-15 - Passes</b>
IIC Rating	<b>ASTM E492 &amp; ASTM E989 - Result: 70</b>
STC Rating	<b>ASTM E90 &amp; ASTM E413 - Result: 67</b>

**SUSTAINABILITY**

Material	<b>Virgin Vinyl</b>
Certification	<b>Floor Score® certified</b>
Environmental Product Declaration	<b>EPD Vinyl Click</b>
Health Product Declaration	<b>HPD 2.1 Vinyl Click - 1000 ppm</b>

**SERVICE**

Warranties	<b>Limited Lifetime Warranty</b>
------------	----------------------------------

