



Technical Recommendation 2022 Season



Pattern	Tire Size	Rim size	Max. neg Camber	Overall diameter	Section width	Tread width	Circumfer. static
			°	mm	mm	mm	mm
Slick F200 (C52)	280/660R18	10.5" x 18"	FA: -4.0 / RA: -3.0	660	304	274	2073
Wet Z207 (W52)	280/660R18	10.5" x 18"	FA: -4.0 / RA: -3.0	660	300	274	2073

Pressures	Front	Rear
	bar	bar
Min. Cold Slick	1.5 - 1.6	1.4 - 1.5
Min. Cold Wet	+0,2 above slick pressure	
Target Hot	2.1 - 2.2	2.1 - 2.3

Temperature	Front	Rear
	°C	°C
Hot operating	90 - 110	90 - 110
Delta in-out	~20	~20

Important remarks

1. Recommended inflation pressure must always be maintained to avoid structural damage to the tire.
2. Turning a tire on the rim or changing position from left to right is prohibited due to rotational direction of the tire.
3. It is highly recommended to use valve caps to avoid pressure leaks.
4. Please check your rims and valves frequently to avoid pressure leaks.

Contact Details

Hankook Tire Europe GmbH

Siemensstr. 14 - 63262 Neu-Isenburg - Germany

Jakub Prasek - Motorsport Support Engineer - eMail: j.prasek@hankookn.com