

DAVIES® Oil Woodstain is lightly pigmented oil-rich finish especially formulated to penetrate wood deeply to highlight grain and protect wood allowing natural beauty of the grain and texture to show.

FEATURES

- Easy to apply to give an even finish
- Penetrate deeply into wood grains for a rich color

SPECIFICATION

PAINT TYPE
Oil Based

PAINT FINISH
Flat

APPLICATION TOOLS
Synthetic Brush/Cloth

PRACTICAL COVERAGE
40-50 sqm/4L/coat
Depending Surface Porosity

PACK SIZE
1L & 4L

COLOR
5 Colors

SHELF LIFE
1 Year when stored in dry and cool conditions

DRYING TIME

Drying Time	: 5-10 hours
Recoating Interval	: 30 minutes-1hour

CLEAN-UP
DAVIES® Paint Thinner

SURFACE PREPARATION

A. New Painting

- All surfaces must be clean, dry, free from dust, dirt, chalk, laitance, efflorescence, rust, grease, oil, and all other foreign materials.
- Sand wood surface until smooth to touch with no slivers or rough edges. Dust off and wipe with a clean rag.
- Patch all holes and imperfections with **DAVIES® 25 Paste Wood** filler or **DAVIES® 77 Laxtite** for clear varnish finish. Use **DAVIES® 790 Speedglaze™ Lacquer Putty** for Duco finish. Sand smooth and dust off.

B. Repainting.

- Use **DAVIES® 300-X Strip-eze™ Paint Remover** to aid in scraping off old paint. Patch all holes and imperfections with **DAVIES® 25 Paste Woodfiller** or **DAVIES® 77 Laxtite™** for clear varnish finish. Use **DAVIES® 790 Speedglaze™ Lacquer Putty** for Duco finish. Sand smooth and dust off.

RECOMMENDED USES



- Furniture



- Cabinets



- Door



- Floor

Full Color



DV 20-40 Maple



DV 20-41 Oak



DV-20-42 Dark Oak



DV 20-90 Brown Mahogany



DV 20-91 Walnut

We have reproduce the Davies Oilwoodstain colors and effects asaccurately as the printing process allows, but due to printing limitations, the colors/effects shown may not mmatch exactly.

APPLICATION METHOD

- Thoroughly mix before and during application for color uniformity.
- For best results, use a synthetic bristle brush because it will hold the stain. Work it down into the wood's surface.
- Color uniformity depends upon even stain distribution. It is important to prevent lap marks during application by following through on a board to a break.
- Apply liberally for uniform coverage and to achieve desired color. If a second coat is desired, allow 8 hours drying before recoating.

PAINTING SYSTEM

Wood Surfaces

	No. of Coats	Product
Woodstain	**1-2**	**DAVIES® Oil Woodstain**
Primer/Sealer	**1**	**DAVIES® Oil 701 Hi-Solids Sanding Sealer**
Topcoat	**2-3**	**DAVIES® Oil 702 Hi-Solids Clear Gloss Lacquer or DAVIES® Oil 703 Hi-Solids Dead Flat Lacquer or DAVIES® Oil 704 Hi-Solids Water White Gloss Lacquer**

STORAGE AND HANDLING

- Keep container closed when not in use.
- Store in a cool, dry and well-ventilated space.
- Do not transfer contents to other containers for storage.
- In case of spillage absorb with inert materials such as sand.