


# Decorative matte coatings with delicate pearl effects

## Pearly Effect

**Davies® Wall Art™ Dolcevita™** gives a modern look to your spaces, a decorative coating characterized by a soft metallic, matte finish and gentle pearls details. With its " washed-out concrete" effect, it fits perfectly into the modern industrials style. Davies® **Wall Art™ Dolcevita™** with a textured , trowelled finish, easy to apply and available in gold and silver finishes.

### RECOMMENDED USES
For cement, metal and wood interior application.

### SPECIFICATION

**PAINT FINISH**
Matte

**COLOR**
Available in 10 standard colors

**PACK SIZE**
1 Liter

**SHELF LIFE**
1 Year when stored in dry and cool conditions

**APPLICATION TOOLS**
Paint Brush/Baby Roller/ Wall Art™ Stainless Steel Trowel

**DRYING TIME**
Drying Time : 24 hours
Recoating Interval : 8 hours

**CLEAN-UP**
Clean Water

### FEATURES
- Solvent-Free & Low VOC
- Environment Friendly
- Water-based
- Durable
- Easy to Clean

### PAINTING SYSTEM

| | No. of Coats | Product | Recommended Coverage m²/1L/coat |
|---|---|---|---|
| Primer/ Sealer | 1 | Davies® Wall Art™ DecoPrime | 7-8 |
| Topcoat | 2 | Davies® Wall Art™ Dolcevita™ | 5-6 |

| | No. of Coats | Product | Recommended Coverage m²/1L/coat |
|---|---|---|---|
| Topcoat | 2 | Davies® Wall Art™ Dolcevita™ | 6-8 |

### STORAGE AND HANDLING
- Keep the container closed when not in use.
- Store in a cool, dry and well-ventilated space.
- Do not transfer contents to other containers for storage.
- In case of spillage absorb with inert materials such as sand.

DAVIES Paint Reinvented

## SURFACE PREPARATION


### Concrete Surfaces


### A. New Painting

- All surfaces must be clean, dry, free from dust, dirt, chalk, laitance, efflorescence, rust, grease, oil, and all other foreign materials.
- Allow new concrete to cure and dry completely for at least 28 days with a moisture content of less than 15% and a Ph level below 10.
- To neutralize and remove efflorescence, treat surfaces with **DAVIES® 100-X Concrete Neutralizer** diluted with 16 parts water to 1 part DV 100-X. Apply by brush or mop to wet surface thoroughly and dry overnight. Rinse with water and dry.
- When applying Rendering Paste or Skimcoat for rough surfaces, concrete may be cured for only 7-14 days. Use **MONDO™ SK-1 Skimcoat Superfine White Powder** or **MONDO™ SK-2 Rendering Paste.**

### B. Repainting

- Remove mold and mildew growth with **DAVIES® 500-X Mildewcide Wash Solution.** Rinse with water, dry and immediately apply the recommended paint system to prevent regrowth of mold and mildew.
- For surfaces that exhibit severe chalk, apply one coat of **DAVIES® 5-530 Liquid Tile™ Penetrating Sealer** or **DAVIES® 555 Concrete Clear Sealer.**
- Repair uneven surfaces with **DAVIES® 5000 Concrete Putty** or **DAVIES® 5-900 Liquid Tile™ Cast.**


3370-02


3371-01


3371-21


3371-30


3370-61


3370-20


3371-31


3370-22


3371-50


3370-90

## APPLICATION



**STEP 1**
Apply one (1) coat of WA-DCP **Wall Art™ Decoprime™** Undercoat Primer using a roller. Let dry for 8 hours.



**STEP 2**
Apply one (1) coat of **Wall Art™ Dolcevita™** using a **Wall Art™ Stainless Steel Trowel** until a compact finish is reached. Let dry for 8 hours.



**STEP 3**
Apply second coat of **Wall Art™ Dolcevita™** as before, then trowel finish to achieve the desired effect.



**STEP 4**
While the surface is still wet, make vertical movements with a **Wall Art™ Stainless Steel Trowel** until the desired texture is reached.
Let dry for 24 hours.

