

Luxe finishes with soft shimmering effects

Soft Shimmering Effect

Davies® Wall Art™ Lune™ is an Italian style decorative finish for interiors, essence of metallic, offered in silver and gold base colours. An exciting, sensitive and intensive finish, for elegant, soft and smooth surroundings, unique and innovative as the light transforms, delicate and elegant as the moonlight.

RECOMMENDED USES

For cement, metal and wood interior application.

FEATURES

- Solvent-Free & Low VOC
- Environment Friendly
- Water-based
- Durable
- Long Lasting Shimmer Gloss Effect

SPECIFICATION

PAINT FINISH
Cement Finish-Flat
Clear-Matte Gloss

COLOR
Available in 10 Standard Colors

PACK SIZE
1 Liter

SHELF LIFE
1 Year when stored in dry and cool conditions

APPLICATION TOOLS
Roller/
Wall Art™ Stainless Steel Trowel

DRYING TIME
Drying Time : 24 hours
Recoating Interval : 8 hours

CLEAN-UP
Clean Water

PAINTING SYSTEM

	No. of Coats	Product	Recommended Coverage m²/1L/coat
Primer/ Sealer	1	Davies® Wall Art™ Decoprime™	7-8
Topcoat	2	Davies® Wall Art™ Lune™	10-12

	No. of Coats	Product	Recommended Coverage m²/1L/coat
Topcoat	2	Davies® Wall Art™ Lune™	10-12

DAVIES Paint Reinvented

SURFACE PREPARATION


Concrete Surfaces

A. New Painting

- All surfaces must be clean, dry, free from dust, dirt, chalk, laitance, efflorescence, rust, grease, oil, and all other foreign materials.
- Allow new concrete to cure and dry completely for at least 28 days with a moisture content of less than 15% and a Ph level below 10.
- To neutralize and remove efflorescence, treat surfaces with **Davies® 100-X Concrete Neutralizer** diluted with 16 parts water to 1 part DV 100-X. Apply by brush or mop to wet surface thoroughly and dry overnight. Rinse with water and dry.
- When applying Rendering Paste or Skimcoat for rough surfaces, concrete may be cured for only 7-14 days. Use **Mondo™ SK-1 Skimcoat Superfine White Powder** or **Mondo™ SK-2 Rendering Paste.**


B. Repainting

- Remove mold and mildew growth with **Davies® 500-X Mildewcide Wash Solution**. Rinse with water, dry and immediately apply the recommended paint system to prevent regrowth of mold and mildew.
- For surfaces that exhibit severe chalk, apply one coat of **DAVIES® 5-530 Liquid Tile™ Penetrating Sealer** or **Davies® 555 Concrete Clear Sealer.**
- Repair uneven surfaces with **Davies® 5000 Concrete Putty** or **Davies® 5-900 Liquid Tile™ Cast.**


3364-90


33365-40


3364-61


3364-01


3364-62


3364-21


3364-30


3365-91


3364-20


3365-92

APPLICATION



STEP 1
Apply one(1) coat of WA-DCP **Wall Art™ Decoprime™** Undercoat Primer using a roller. Let dry for 8 hours.



STEP 2
Apply one(1) thin coat of **Wall Art™ Lune™** using a **Wall Art™** Stainless Steel Roller. While the layer is still wet, make small rotation movements with a Wall Art™ Stainless Steel Trowel. Let dry for at least 8 hours.



STEP 3
Apply the second coat of **Wall Art™ Lune™** with a more generous quantity of product using **Wall Art™** Stainless Steel Trowel, then make movements as previously described until a velvety effect is reached.

STORAGE AND HANDLING

- Keep the container closed when not in use.
- Store in a cool, dry and well-ventilated space.
- Do not transfer contents to other containers for storage.
- In case of spillage absorb with inert materials such as sand.