

Paiternly textures that evoke a rustic Italian ambiance

Rustic Italian Finish

Davies® Wall Art™ Maestró lets you recreate intricate works of Italian craftmanship in your home with its distinctive special effects that turn ordinary walls into extraordinary masterpieces. **Davies® Wall Art™ Maestró** is formulated wlth low Volatile Organlc Compound, contains no lead or mercury and is formaldehyde-free.

RECOMMENDED USES
For cement, metal and wood interior application.

FEATURES
- Solvent-Free & Low VOC
- Environment Friendly
- Water-based
- Durable
- Washable

SPECIFICATION

PAINT FINISH
Matte

COLOR
Available in 10 standard colors

PACK SIZE
1 Liter

SHELF LIFE
1 Year when stored in dry and cool conditions

APPLICATION TOOLS
Paint Brush/Baby Roller/ Wall Art™ Spalter Brush (thin brittles)

DRYING TIME
Drying Time : 24 hours
Recoating Interval : 8 hours

CLEAN-UP
Clean Water

PAINTING SYSTEM

	No. of Coats	Product	Recommended Coverage m²/1L/coat
Primer/Sealer	1	Davies® Wall Art™ 1350 Concrete Primer & Sealer	7-8
Topcoat	2	Davies® Wall Art™ Maestró Topcoat	10-12

DAVIES Paint Reinvented

SURFACE PREPARATION

Concrete Surfaces

A. New Painting


- All surfaces must be clean, dry, free from dust, dirt, chalk, laitance, efflorescence, rust, grease, oil, and all other foreign materials.
- Allow new concrete to cure and dry completely for at least 28 days with a moisture content of less than 15% and a Ph level below 10.
- To neutralize and remove efflorescence, treat surfaces with **DAVIES® 100-X Concrete Neutralizer** diluted with 16 parts water to 1 part DV 100-X. Apply by brush or mop to wet surface thoroughly and dry overnight. Rinse with water and dry.
- When applying Rendering Paste or Skimcoat for rough surfaces, concrete may be cured for only 7-14 days. Use **MONDO™ SK-1 Skimcoat Superfine White Powder** or **MONDO™ SK-2 Rendering Paste.**

B. Repainting

- Remove mold and mildew growth with **DAVIES® 500-X Mildewcide Wash Solution**. Rinse with water, dry and immediately apply the recommended paint system to prevent regrowth of mold and mildew.
- For surfaces that exhibit severe chalk, apply one coat of **DAVIES® 5-530 Liquid Tile™ Penetrating Sealer** or **DAVIES® 555 Concrete Clear Sealer.**
- Repair uneven surfaces with **DAVIES® 5000 Concrete Putty** or **DAVIES® 5-900 Liquid Tile™ Cast.**


3530-62



3530-31


3530-91


3530-30


3530-10


3530-92


3530-21


3530-90


3530-40


3530-63

APPLICATION



STEP 1
Apply one(1) coat of **DAVIES® 1350 Megacryl® Concrete Primer & Sealer** using a roller. Let dry for 8 hours.



STEP 2
Apply one(1) coat to two (2) coats of **Wall Art™ Maestró** with irregular cries-cross movements using spalter brush, taking care not to cover surfaces more than two (2) sq.m at one time.



STEP 3
After 20-30 minutes (while the paint is semi-dry). slightly press down the surface using **Wall Art™ Plastic Spatula** to achieve the desired textured effect.

STORAGE AND HANDLING

- Keep the container closed when not in use.
- Store in a cool, dry and well-ventilated space.
- Do not transfer contents to other containers for storage.
- In case of spillage absorb with inert materials such as sand.