

Textured decorative coating with metallic effect

Metallic Effect

Water-based decorative paint formulated with special metallescent pigments, that together with specific research on colour tinting, is able to imitate the colours and reflectionsof prestigious metals, minerals and precious stones. Very easy to apply, and free from solvents and volatile organic compounds, In full respect for man and the environment.

RECOMMENDED USES
For cement, metal and wood interior application.

FEATURES
- Solvent-Free & Low VOC
- Environment Friendly
- Water-based
- Good Hiding
- Good Gloss Retention

SPECIFICATION

PAINT FINISH
Gloss

COLOR
Available in 10 standard colors

PACK SIZE
1 Liter

SHELF LIFE
1 Year when stored in dry and cool conditions

APPLICATION TOOLS
Paint Brush/Baby Roller/ Wall Art™ Spalter Brush

DRYING TIME
Drying Time : 4-6 hours
Recoating Interval : 2 hours

CLEAN-UP
Clean Water

PAINTING SYSTEM

	No. of Coats	Product	Recommended Coverage m²/1L/coat
Primer/ Sealer	1	Davies® Wall Art™ Metal Fond	7-8
Topcoat	2	Davies® Wall Art™ Metal	10-12

STORAGE AND HANDLING
- Keep the container closed when not in use.
- Store in a cool, dry and well-ventilated space.
- Do not transfer contents to other containers for storage.
- In case of spillage absorb with inert materials such as sand.

DAVIES® Paint Reinvented

SURFACE PREPARATION

Concrete Surfaces

A. New Painting


- All surfaces must be clean, dry, free from dust, dirt, chalk,laitance, efflorescence, rust, grease, oil, and all other foreign materials.
- Allow new concrete to cure and dry completely for at least 28 days with a moisture content of less than 15% and a Ph level below 10.
- To neutralize and remove efflorescence, treat surfaces with **DAVIES® 100-X Concrete Neutralizer** diluted with 16 parts water to 1 part DV 100-X. Apply by brush or mop to wet surface thoroughly and dry overnight. Rinse with water and dry.
- When applying Rendering Paste or Skimcoat for rough surfaces, concrete may be cured for only 7-14 days. Use **MONDO™ SK-1 Skimcoat Superfine White Powder** or **MONDO™ SK-2 Rendering Paste.**


B. Repainting

- Remove mold and mildew growth with DAVIES® 500-X Mildewcide Wash Solution. Rinse with water, dry and immediately apply the recommended paint system to prevent regrowth of mold and mildew.
- For surfaces that exhibit severe chalk, apply one coat of **DAVIES® 5-530 Liquid Tile™ Penetrating Sealer** or **DAVIES® 555 Concrete Clear Sealer.**
- Repair uneven surfaces with **DAVIES® 5000 Concrete Putty** or **DAVIES® 5-900 Liquid Tile™ Cast.**


3729-41


3729-50


3734-62



3734-01


3729-12


3734-61


3734-30


3734-40


3729-90


3734-02

APPLICATION



STEP 1

Apply one (1) Coat of WA-MFP **Wall Art™ Metal™ Fond** using a roller or brush in irregular criss cross movements to highlight the chromatic effect. Let dry for 8 hours.



STEP 2

Apply one (1) coat of Wall Art™ Metal™ using a roller or Wall Art™ Spalter Brush in similar irregular criss cross strokes or, alternatively, by using a glove to apply the product using circular movements. Let dry for 2 hours.



STEP 3

Apply second coat of Wall Art™ Metal™ using the same technique used for the first coat. Let dry for 4 to 6 hours.

