Exquisite decorative coatings with metallic effects

DAVIES
Paint Reinvented

Wall Art™ METAL™

Wall Art™ METAL™



3729-41





3734-62



3729-12



3734-30



3734-61



3729-50



3729-90



3734-40



3734-01



3734-02

Wall Art™ METAL™ is a water-based decorative paint formulated with special metallescent pigments. Using scientific color tinting methods, this special finish demonstrates an ability to imitate the texture and luster of precious metals, minerals, and precious stones. **Wall Art™ METAL™** is also free from solvents and volatile organic compounds — giving your spaces beauty and luxury that is safe for the health and the environment.

Due to computer monitor limitations, colors seen here may not accurately reflect Davies Paints colors.
To confirm your color choices, please refer to our color chips available in DIY and hardware stores or call (02) 8570-7000 for assistance.

Wall Art™ METAL™

Types of Substrate:
Cement, metal, wood; for interior application

Colors:
Available in oro and argento finishes, 10 standard colors (other colors as requested)

Mixing directions:
Stir gently by hand before application.

Reduction:
Use as is, Do not thin down.


Cleaning:
Wash with tap water

Application tools:
Paint Brush/Baby Roller
Wall Art™ Spalter Brush (thin brittles)


Coverage:
Wall Art™ Metal Fond™ - 7.5-8 square meters / liter / coat
Wall Art™ Metal™ Topcoat - 10-12 square meters / liter / 2 coats

Preparation of the Substrate:
1. Make sure that the surface is clean and dry, free of dust, oil, laitance, paint, curing compounds, and other contaminants such as algae and mildew.
2. Scrape off any cement residue and loose material, and sand away rough edges for a smooth surface.
3. Surface must be cured for 28 days (or 5-7 days skimcoat preparation) before application.

Product Application Procedure:



STEP 1
Apply one (1) coat of **Wall Art™ Metal Fond™** using a roller or brush in irregular criss cross movements to highlight the chromatic effect. Let dry for 8 hours.



STEP 2
Apply one (1) coat of **Wall Art™ Metal ™** using a roller or spalter brush in similar irregular criss cross strokes or, alternatively, by using a glove to apply the product using circular movements. Let dry for 2 hours.



STEP 3
Once dry, apply the second coat using the same technique you used for the first coat. Let dry for 4-6 hours.

Visualize your space in different colors ! Download the DAVIES ColorStudio App now.

DAVIES ColorStudio
Download on the App Store
GET IT ON Google Play

Davies Paints Philippines, Inc.
1415 A. Sandoval Ave., cor. Mercedes Ave., San Miguel, Pasig City 1600, Philippines

(02) 8570-7000
Customer Care Hotline
www.daviespaints.com.ph
https://www.facebook.com/DaviesPaintsPhilippines
http://instagram.com/daviespaints

ISSUE NO. 1