Avante Transport 5000 Plus

Veterinary Anesthesia Machine

Ideal for traveling vets, and office-based surgery centers and small facilities

The Transport 5000 Plus saves time during mobile animal hospital rescues, field research, and house calls. Cost-effective to save you money, the Transport 5000 Plus has integrated safety functions and is easy to use and maintain.

GAS SUPPLY

- > Pipeline gas: O2
- Output pressure of regulator: 280 kPa - 300 kPa
- Security valve discharge pressure: ≤ 600 kPa
- Pressure of pipeline inlet: 280 kPa - 600 kPa

RESPIRATION SYSTEM

- > Absorbent: 1000 mL
- System leakage: When pressure is lower than 3 kPa, ≤ 125 mL/min
- > System compliance: ≤ 4 mL/kPa
- > Resistance of ventilator system:
 - > Flow-rate: 30L/min < 0.16kPa
 - > Flow-rate: 60L/ min < 0.52kPa
 - > APL valve ~0.19 6 kPa

FLOWMETER

- > Gas: scale
- > O2: 0.0 L/min ~10 L/min
- Precision: At 20, atmospheric pressure is 101.3 kPa, the precision of flowmeter is level: 2.5
- > O2 flushing: 35 L/min ~ 75 L/min

SPECIFICATIONS



Weight: 45 lbs (20 kgs)



Length: 11.41" (29 cm)

Width: 19.29" (49 cm)

Height: 20.47" (52 cm)



521-2022-01-31

