

Ohmeda Excel 110/210

Anesthesia Machine

Equipment for the way *you* operate



Certified Refurbished

Your pneumatic solution for surgeries in **close quarters**

The compact Excel 110 and 210 come standard with O₂ and N₂O, as well as a Hypoxic Guard and a GMS absorber. The Excel 210 also includes medical air.



Pictured: Excel 210
Color and drawer pack
configurations may
vary from picture.

► A Quick Look

Features

- Accommodates three gases and two vaporizers
- Powerful ventilation and monitoring capabilities for secondary anesthetizing locations.

Options

- 7800 Electronic Ventilator with Tek 5 Vaporizers
- 7000 Ventilator with Tek 4 Vaporizers
- New Sigma Delta Vaporizer

Ohmeda Excel 110/210

Anesthesia Machine

Equipment for the way *you* operate

Specifications for the Excel 110

Weight (approximate) 270 lbs. (122 kg)

Options

–Vaporizer 17 lbs. (7.6 kg)

–Absorber 21 lbs. (9.5 kg)

–Ventilator 19 lbs. (8.5 kg)

Dimensions

Height 66" (168 cm)

from floor to upper most part of top shelf

Depth 30" (76 cm)

with casters and brake bar

Width

–Machine only 20" (50.7 cm)

–Machine with monitor pod 27" (68 cm)

–Absorber and Absorber Arm Add 10" (25.5 cm)

Shelving Systems

Middle Shelf

–Maximum Load 24 lbs. (11 kg)

–Usable height 6" (15.2 cm)

–Shelf Size 16.6" x 12.5" (42 cm x 31.7 cm)

varies slightly with shelf style

Top Shelf

–Maximum Load 48 lbs. (22 kg)

–Shelf Size 21.5" x 14.2" (54.5 cm x 36 cm)

varies slightly with shelf style

Table-top

–Height (above floor) 33.5" (84 cm)

–Size 20" x 11.7" (50.8 cm x 29 cm)

varies slightly with shelf style

Drawer Cabinet

–Contains two 15.5" x 10.5" x 4" (39.4 cm x 26.7 cm x 10.2 cm) drawers

Absorber Post Mounting Assembly

–Absorber Arm Length 14" (35.5 cm)

varies slightly with arm style

–Vertical Adj (above floor) 10" to 26" (25.4 cm to 66 cm)

–Horizontal Adj 6.5" to 11" (16.5 cm to 27.9 cm)

Casters

Diameter 5" (12.7 cm)

front casters have a foot-operated brake-bar lock

Common Gas Outlet

–Equipped with a latching, positive engagement, bayonet type connector. The common gas outlet connector will also accept standard 22 mm OD or 15 mm ID conical friction fit connectors.

Specifications for the Excel 210

Weight (approximate) 300 lbs. (136 kg)

Options

–Vaporizer 17 lbs. (7.6 kg)

–Absorber 21 lbs. (9.5 kg)

–Ventilator 19 lbs. (8.5 kg)

Dimensions

Height 66" (168 cm)

from floor to upper most part of top shelf

Depth 30" (76 cm)

with casters and brake bar

Width

–Machine only 22" (55.8 cm)

–Machine with monitor pod 29" (73.6 cm)

–Absorber and Absorber Arm Add 10" (25.5 cm)

Shelving Systems

Middle Shelf

–Maximum Load 24 lbs. (11 kg)

–Usable height 6" (15.2 cm)

–Shelf Size 18.6" x 12.5" (47.2 cm x 31.7 cm)

varies slightly with shelf style

Top Shelf

–Maximum Load 48 lbs. (22 kg)

–Shelf Size 23.5" x 14.2" (59.6 cm x 36 cm)

varies slightly with shelf style

Table-top

–Height (above floor) 33.5" (84 cm)

–Size 21.7" x 11.7" (55 cm x 29 cm)

varies slightly with shelf style

Drawer Cabinet

–Contains two 15.5" x 10.5" x 4" (39.4 cm x 26.7 cm x 10.2 cm) drawers

Absorber Post Mounting Assembly

–Absorber Arm Length 14" (35.5 cm)

varies slightly with arm style

–Vertical Adj (above floor) 10" to 26" (25.4 cm to 66 cm)

–Horizontal Adj 6.5" to 11" (16.5 cm to 27.9 cm)

Casters

Diameter 5" (12.7 cm)

front casters have a foot-operated brake-bar lock

Common Gas Outlet

–Equipped with a latching, positive engagement, bayonet type connector. The common gas outlet connector will also accept standard 22 mm OD or 15 mm ID conical friction fit connectors.