

Benefits

- A high-quality louver with an anodized aluminum finish
- Low glare rating (UGR<19) with high level of visual comfort
- Wide batwing light distribution to ensure stable and uniform distribution of light

Application



Library



Shopping Mall



Office



Hospital



School

Model	Item Description	W	PF	lm	lm/w	CRI	Beam	Life	Single Box (LxWxH)mm	Outer Box (LxWxH)mm	Packing Qty (PCS/CTN)
FLP70000v0-SV	GABIO PENDANT LV 20W 4000K 90D	20	0.9	2000	100	80	90°	50000	60*70*1160	200*145*1170	6

Application Conditions	
IP	IP20
Operating Temperature	-20~40°C
Application Temperature	25°C
Storage Environment	-25~50°C


Mechanical Properties	
Optical Material	Reflector
Housing Material	Aluminium
Finishing Colour	Silver

Electrical Supply	
Frequency (Hz)	50/60
Voltage (V)	220-240
AC/DC	AC

Accessories

Photo	Model	Item Description	Single Box (LxWxH)mm	Outer Box (LxWxH)mm	Packing Qty (BAG/CTN)
	LA6004	GABIO MAIN SUPPLY WIRE	/	/	100
	LA6006	GABIO SUSPENSION WIRE	/	/	120
	LA6008-SV-4000K	GABIO L-JOINT	100*120*70	430*250*340	40
	LA6009-SV-4000K	GABIO T-JOINT	700*110*155/	340*570*220	30
	LA6010-SV-4000K	GABIO X-JOINT	340*590*220	140*160*70	30

Dimensional Drawing



FLP70000v0