

SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name BELTGRIP (AEROSOL)

Synonym(s) 3081 - PRODUCT CODE • BELT GRIP • BELTGRIP 3081 • CRC BELTGRIP (AEROSOL)

1.2 Uses and uses advised against

Use(s) BELT GRIP • TACKIFIER

1.3 Details of the supplier of the product

Supplier name CRC INDUSTRIES (AUST) PTY LIMITED

Address 9 Gladstone Road, Castle Hill, NSW, 2154, AUSTRALIA

Telephone (02) 9849 6700

Fax (02) 9680 4914

Email info@crcind.com.au

Website www.crcindustries.com.au

1.4 Emergency telephone number(s)

Emergency 13 11 26 (PIC)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO AUSTRALIAN WHS REGULATIONS

GHS classification(s) Aerosols - Flammable: Category 1

Aerosols - Pressurised: Category 1 Skin Corrosion/Irritation: Category 2

Specific Target Organ Systemic Toxicity (Single Exposure): Category 3

Aquatic Toxicity (Chronic): Category 1

2.2 Label elements

Signal word DANGER

Pictogram(s)







Hazard statement(s)

H222 Extremely flammable aerosol.

H229 Pressurized container: may burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H410 Very toxic to aquatic life with long lasting effects.



SDS Date: 20 Jul 2016

Version No: 2.1

Prevention statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response statement(s)

P304 + P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P321 Specific treatment is advised - see first aid instructions.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before re-use.

P391 Collect spillage.

Storage statement(s)

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C.

Disposal statement(s)

P501 Dispose of contents/container in accordance with relevant regulations.

2.3 Other hazards

No information provided.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
N-HEPTANE	142-82-5	205-562-2	80%
LIQUEFIED PETROLEUM GAS (CONTAINS <0.1% 1,3 BUTADIENE)	68476-85-7	270-704-2	10 to 30%

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to

stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or

an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.

Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

Ingestion For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If

swallowed, do not induce vomiting. Ingestion is considered unlikely due to product form.

First aid facilities No information provided.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways.



5.2 Special hazards arising from the substance or mixture

Highly flammable aerosol. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition. Aerosol may explode at temperatures exceeding 50°C. Eliminate all ignition sources, including cigarettes, open flames, spark producing switches/tools, heaters, pilot lights, mobile phones, etc when handling. Aerosol cans may explode above 50°C.

5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

2Y

- 2 Fine Water Spray.
- Y Risk of violent reaction or explosion. Wear full fire kit and breathing apparatus. Contain spill and run-off.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool (< 50°C), dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure aerosol containers/ cans are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for damaged/leaking containers. Large storage areas should have appropriate fire protection systems.

7.3 Specific end use(s)

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m³	ppm	mg/m³
Liquefied petroleum gas (LPG)	SWA (AUS)	1000	1800	1000	1800
n-Heptane	SWA (AUS)	400	1600	500	2050

Biological limits

No biological limit values have been entered for this product.

8.2 Exposure controls

Engineering controls

Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Flammable vapours may accumulate in poorly ventilated or confined areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back. Maintain vapour levels below the recommended exposure standard.

ChemAlert.

SDS Date: 20 Jul 2016 Version No: 2.1

Page 3 of 7

PPE

Eye / Face Wear splash-proof goggles. Hands Wear nitrile or neoprene gloves.

Body When using large quantities or where heavy contamination is likely, wear coveralls.

Respiratory At high vapour levels, wear a Type A-Class P1 (Organic gases/vapours and Particulate) respirator.





9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

VISCOUS CLEAR LIQUID (AEROSOL DISPENSED) **Appearance**

NOT AVAILABLE

Odour ETHEREAL ODOUR **Flammability** HIGHLY FLAMMABLE Flash point -4°C (n-Heptane) **Boiling point NOT AVAILABLE**

Melting point $< 0^{\circ}C$

NOT AVAILABLE Evaporation rate Hq NOT AVAILABLE Vapour density NOT AVAILABLE Specific gravity NOT AVAILABLE Solubility (water) **INSOLUBLE** Vapour pressure NOT AVAILABLE Upper explosion limit NOT AVAILABLE Lower explosion limit 1.05 % (n-Heptane) Partition coefficient **NOT AVAILABLE** Autoignition temperature **NOT AVAILABLE** Decomposition temperature NOT AVAILABLE **NOT AVAILABLE** Viscosity **Explosive properties NOT AVAILABLE** Oxidising properties **NOT AVAILABLE**

9.2 Other information

Odour threshold

80 % (n-Heptane) % Volatiles

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Polymerization is not expected to occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), heat and ignition sources.

10.6 Hazardous decomposition products

May evolve carbon oxides and hydrocarbons when heated to decomposition.



SDS Date: 20 Jul 2016 Version No: 2.1

Page 4 of 7

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity Information available for the product:

Based on available data, the classification criteria are not met. This product may have the potential to cause

adverse health effects if intentionally misused (e.g. deliberately inhaling contents).

Information available for the ingredient(s):

Ingredient	Oral Toxicity	Dermal Toxicity	Inhalation Toxicity
	(LD50)	(LD50)	(LC50)
N-HEPTANE			103 g/m³/4 hours (rat)

Skin Contact may result in drying and defatting of the skin, rash and dermatitis.

Eye Contact may result in irritation, lacrimation, pain and redness.

Sensitisation Not classified as causing skin or respiratory sensitisation.

Mutagenicity

Not classified as a mutagen.

Carcinogenicity

Not classified as a carcinogen.

Not classified as a carcinogen.

Reproductive Not classified as a reproductive toxin.

STOT – single Over exposure may result in irritation of the nose and throat, coughing and headache. High level exposure

exposure may result in nausea, dizziness and drowsiness.

STOT – repeated exposure

Not classified as causing organ damage from repeated exposure.

Aspiration Not classified as causing aspiration.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

12.2 Persistence and degradability

No information provided.

12.3 Bioaccumulative potential

No information provided.

12.4 Mobility in soil

No information provided.

12.5 Other adverse effects

No information provided.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal For small amounts, absorb contents with sand or similar and dispose of to an approved landfill site. Do not

puncture or incinerate aerosol cans. Contact the manufacturer/supplier for additional information (if required).

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE





	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	1950	1950	1950
14.2 Proper Shipping Name	AEROSOLS	AEROSOLS	AEROSOLS
14.3 Transport Hazard Class	2.1	2.1	2.1
14.4 Packing Group	None Allocated	None Allocated	None Allocated

14.5 Environmental hazards No information provided

14.6 Special precautions for user

 Hazchem code
 2Y

 GTEPG
 2D1

 EMS
 F-D, S-U

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule Classified as a Schedule 5 (S5) Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Classifications Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and

Labelling of Chemicals.

The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous

Substances [NOHSC: 1008(2004)].

Hazard codes F Flammable

N Dangerous for the environment

Xi Irritant Xn Harmful

Risk phrases R11 Highly flammable.

R38 Irritating to skin.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R67 Vapours may cause drowsiness and dizziness.

Safety phrases S2 Keep out of reach of children.

S9 Keep container in a well ventilated place.

S16 Keep away from sources of ignition - No smoking.

S29 Do not empty into drains.

S33 Take precautionary measures against static discharges.

S60 This material and its container must be disposed of as hazardous waste.

S61 Avoid release to the environment. Refer to special instructions/safety data sheets.
S62 If swallowed, do not induce vomiting; seek medical advice immediately and show this

container or label.

Inventory listing(s) AUSTRALIA: AICS (Australian Inventory of Chemical Substances)

All components are listed on AICS, or are exempt.

16. OTHER INFORMATION

Additional information A

AEROSOL CANS may explode at temperatures approaching 50°C.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.



PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations

ACGIH American Conference of Governmental Industrial Hygienists

CAS # Chemical Abstract Service number - used to uniquely identify chemical compounds

CNS Central Nervous System

EC No. EC No - European Community Number

EMS Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous

Goods)

GHS Globally Harmonized System

GTEPG Group Text Emergency Procedure Guide IARC International Agency for Research on Cancer

LC50 Lethal Concentration, 50% / Median Lethal Concentration

LD50 Lethal Dose, 50% / Median Lethal Dose

mg/m³ Milligrams per Cubic Metre
OEL Occupational Exposure Limit

pH relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly

alkaline).

ppm Parts Per Million

STEL Short-Term Exposure Limit

STOT-RE Specific target organ toxicity (repeated exposure)
STOT-SE Specific target organ toxicity (single exposure)

SUSMP Standard for the Uniform Scheduling of Medicines and Poisons

SWA Safe Work Australia
TLV Threshold Limit Value
TWA Time Weighted Average

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794

Email: info@rmt.com.au Web: www.rmt.com.au.

[End of SDS]

