Terminal Blocks

multicomp PRO

RoHS Compliant





Specifications


Current Rating : 25 Amp AC300V Insulation withstands Volt : AC2000V min. Insulation Resistance : >2000M Ω DC500V Operation Temperature : -40°C to +120°C Wire Range : 12AWG to 22AWG

Screw Torque : 16lb-inch

Diagram







Dimensions: Millimetres

Pitch: 11	tch: 11mm				
Poles	Α	В			
2	24.7mm	11mm			
3	35.7mm	22mm			
5	57.7mm	44mm			
7	79.7mm	66mm			
9	101.7mm	88mm			

SL	Material		Plating/Finish	Remark
1	Insulating Body	PBT(UL94V-0)	-	Black
2	Terminal	Brass	Tin Plated	-
3	Screw	Steel	Zinc Plated	-
4	Cover	PC	-	-

Part Number Table

Description	Part Number
Barrier Terminal Block, 11mm, 25A 300V, with cover, 2 Poles	MC002087
Barrier Terminal Block, 11mm, 25A 300V, with cover, 3 Poles	MC002088
Barrier Terminal Block, 11mm, 25A 300V, with cover, 5 Poles	MC002089
Barrier Terminal Block, 11mm, 25A 300V, with cover, 7 Poles	MC002090
Barrier Terminal Block, 11mm, 25A 300V, with cover, 9 Poles	MC002091

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

