NSYS3D7525P

Spacial S3D plain door with mount.plate. H700xW500xD250.IP66 IK10 RAL7035.





Main

Range	Spacial	
Product name	Spacial S3D	
Application	Multi-purpose	
Category	Compact enclosure	
Enclosure nominal height	700 mm	
Enclosure nominal width	500 mm	
Enclosure nominal depth	250 mm	
Door type	Plain	
Mounting plate description	Plain	
Type of gland plate	Standard	
Installation accessory type	Wall-mounting	
Device composition	1 body 1 mounting plate 1 door with lock 1 cable gland plate	

Complementary

Body type	Gutter-shaped front rail double sheet thickness
body type	·
	Single piece body
Number of doors	Front face: 1 door(s)
Door opening side	Reversible (120 °)
Lock type	3 points lock, 3 mm double-bar
Accessibility for operation	Front
Removable parts	Door by hinges
	Cable gland plate by screws
	Mounting plate by fixing element
Material	Enclosure: steel
iviateriai	Mounting plate: galvanised steel
	Mounting place, galvanised steel
Surface finish	Enclosure: epoxy-polyester powder
Colour	Enclosure: grey (RAL 7035)
Standards	IEC 62208
Product certifications	cUL[RETURN]GL[RETURN]LR[RETURN]UL[RETURN]DNV[RETURN]BV
Net weight	19 kg

Environment

NEMA degree of protection	NEMA 4X/13
IK degree of protection	IK10 conforming to IEC 62262
IP degree of protection	IP66 conforming to IEC 60529

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	29.5 cm
Package 1 Width	51.5 cm
Package 1 Length	71.5 cm
Package 1 Weight	19.07 kg
Unit Type of Package 2	P12
Number of Units in Package 2	12
Package 2 Height	157.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	243.0 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	[™] China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------