

No. 1907/2006 (REACH)
Printed 05.08.2019

revision 04.09.2018 (GB) Version 9.0

Flex 310 PU

## ! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product Flex 310 PU Code-Nr. 133020

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

1-Component Adhesives and Sealants, permanently elastic

1.3. Details of the supplier of the safety data sheet

**Distributor** WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

Phone: +49(0)251 / 9322 - 0, Fax: +49(0)251 / 9322 - 244

E-Mail: msds@weicon.de Internet: www.weicon.de

Advice Produktsicherheit / Product-Safety-Department

Phone : +49(0)251 / 9322 - 0 Fax : +49(0)251 / 9322 - 244 E-mail (competent person):

msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:

++44 1865 407333 (English)

TRANSPORT EMERGENCY CONTACT - UK, UAE, South

Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):

Tel: ++49 69 222 25285 (Deutsch, Englisch)

#### ! SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard

Hazard Statements Classification procedure

categories

Resp. Sens. 1 H334

**Hazard Statements** 

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

2.2. Label elements



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 04.09.2018 (GB) Version 9.0

Flex 310 PU

## Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS08

## Signal word

Danger

#### **Hazard Statements**

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### **Precautionary Statements**

P102 Keep out of reach of children.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P285 In case of inadequate ventilation wear respiratory protection.

P304 + P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

P501 Dispose of contents/container to hazardous or special waste collection point.

#### Hazardous ingredients for labeling

4,4-Methylendiphenyldiisocyanat, Oligomere

## ! Special rules for supplemental label elements for certain mixtures

Persons already sensitised to diisocyanates may develop allergic reactions when using this product.

Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1according to standard EN 14387) is used.

Contains isocyanates. May produce an allergic reaction.

#### 2.3. Other hazards

People who suffer from skin sensitazion problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this preparation.

## Information pertaining to special dangers for human and environment

May cause sensitization by inhalation.

#### Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## ! SECTION 3: Composition/ information on ingredients

#### 3.1. Substances

not applicable

#### 3.2. Mixtures

#### ! Description

Preparation of different active substances

#### **Hazardous ingredients**



No. 1907/2006 (REACH) Printed 05.08.2019

revision 04.09.2018 (GB) Version 9.0

Flex 310 PU

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
101-68-8	202-966-0	4,4'-methylenediphenyl diisocyanate	< 0,5	Carc. 2, H351 / Acute Tox. 4, H332 / STOT RE 2, H373 / Eye Irrit. 2, H319 / STOT SE 3, H335 / Skin Irrit. 2, H315 / Resp. Sens. 1, H334 / Skin Sens. 1, H317
4083-64-1	223-810-8	tosyl isocyanate	< 0,1	Eye Irrit. 2, H319 / STOT SE 3, H335 / Skin Irrit. 2, H315 / Resp. Sens. 1, H334
25686-28-6	500-040-3	4,4-Methylendiphenyldiisocyanat, Oligomere	< 0,2	Resp. Sens. 1, H334 / Carc. 2, H351 / STOT RE 2, H373 / Acute Tox. 4, H332 / Skin Irrit. 2, H315 / Eye Irrit. 2, H319 / Skin. Sens. 1, H317 / STOT SE 3, H335
90622-57-4	918-167-1	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	< 2	Flam. Liq. 3, H226 / Asp. Tox. 1, H304 / Aquatic Chronic 4, H413
1330-20-7	215-535-7	xylene	< 5	Flam. Liq. 3, H226 / STOT RE 2, H373 / Asp. Tox. 1, H304 / Acute Tox. 4, H312, H332 / Skin Irrit. 2, H315 / Eye Irrit. 2, H319 / STOT SE 3, H335

#### **REACH**

CAS No	Name	REACH registration number
101-68-8	4,4'-methylenediphenyl diisocyanate	01-2119457014-47
4083-64-1	tosyl isocyanate	01-2119980050-47
25686-28-6	4,4-Methylendiphenyldiisocyanat, Oligomere	01-2119457013-49
90622-57-4	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	01-2119472146-39
1330-20-7	xylene	01-2119488216-32

## ! Additional advice

EG: 918-167-1: Outside Europe, this substance is assigned the CAS no. 90622-57-4 (isoparaffins [isoalkanes]); (Content of aromatics <2%)

#### **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### **General information**

Remove contaminated soaked clothing immediately.

## In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

## In case of skin contact

Dab affected skin part with a cotton ball or cellulose and wash it afterwards with plenty of water and a mild cleaner. Consult a doctor if skin irritation persists.

## In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

## In case of ingestion

Do not induce vomiting.

Call for a doctor immediately.

## 4.2. Most important symptoms and effects, both acute and delayed

No information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No information available.



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 04.09.2018 (GB) Version 9.0

Flex 310 PU

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

## Suitable extinguishing media

Alcohol-resistant foam

Dry powder

Carbon dioxide

#### Unsuitable extinguishing media

water

#### 5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

Nitrogen gases (NOx)

Sulfur oxide

Hydrogen chloride (HCI)

#### 5.3. Advice for firefighters

#### Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

#### **Additional information**

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

## **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

## For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.

#### 6.2. Environmental precautions

Do not discharge into the drains or bodies of water..

Do not discharge into the drains/surface waters/groundwater.

## 6.3. Methods and material for containment and cleaning up

Take up mechanically and send for disposal.

#### 6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13

Personal protection equipment: see section 8

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

## Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

#### General protective measures

Do not inhale vapours.

Avoid contact with eyes and skin



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 04.09.2018 (GB) Version 9.0

Flex 310 PU

#### Hygiene measures

At work do not eat, drink and smoke.

Keep away from food and drink.

Keep separated from food and feed.

Wash hands before breaks and after work.

## Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking Vapours can form an explosive mixture with air.

## 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Prevent penetration into the ground.

## Advice on storage compatibility

Do not store with acids or alkalies.

Do not store together with animal feedstuffs.

Do not store together with food.

## Further information on storage conditions

Keep container tightly closed and store at cool and aired place.

Protect from frost.

Protect from heat and direct solar radiation.

Store in a dry place.

Protect from heat/overheating.

## 7.3. Specific end use(s)

## Recommendation(s) for intended use

See section 1.2

## ! SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
1330-20-7	Xylene, o-, m-, p- or mixed isomers	8 hours	220	50	EH40/2005
		Short-term	441	100	

# DNEL-/PNEC-values DNEL worker

CAS No	Substance name	Value	Code	Remark
101-68-8	4,4'-methylenediphenyl diisocyanate	0,1 mg/m3	DNEL acute inhalative (systemic)	
		0,05 mg/m3	DNEL long-term inhalative (local)	
		0,1 mg/m3	DNEL long-term oral (repeated)	
		50 mg/kg bw/day	DNEL acute dermal, short-term (systemic)	
		28,7 mg/cm2	DNEL acute dermal, short-term (local)	
		0,05 mg/m3	DNEL long-term inhalative (systemic)	
1330-20-7	xylene	289 mg/m3	DNEL acute inhalative (systemic)	
		77 mg/m3	DNEL long-term inhalative (systemic)	
		180 mg/kg	DNEL long-term dermal (systemic)	



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 04.09.2018 (GB) Version 9.0

Flex 310 PU

CACNO	Cubatanaa nama	Value	Codo	Domonic
CAS No	Substance name	Value	Code	Remark
		289 mg/m3	DNEL acute inhalative (local)	
		289 mg/m3	DNEL acute inhalative (local)	
PNEC				
CAS No	Substance name	Value	Code	Remark
1330-20-7	xylene	12,46 mg/kg	PNEC sediment, marine water	
		0,327 mg/l	PNEC aquatic, marine water	
		12,46 mg/kg	PNEC sediment, freshwater	
		0,327 mg/l	PNEC aquatic, freshwater	
		2,31 mg/kg	PNEC sediment, freshwater	

#### ! Additional advice

The statutory local and national regulations have to be observed.

## 8.2. Exposure controls

## Respiratory protection

If ventilation insufficient, wear respiratory protection.

Short-term: filter apparatus, filter A2/P2, otherwise environment-independent breathing apparatus.

#### Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: fluorinated rubber; 0,7mm; 480min; 60min;

## Eye protection

tightly fitting goggles

#### Other protection measures

protective clothing

## Appropriate engineering controls

Sufficient ventilation and exhaustion.

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

AppearanceColourOdourpastyvarioussolvent-like

# Odour threshold not determined

Important health, safety and environmental information

Value Temperature at Method F	Remark
-------------------------------	--------

pH value not determined

boiling point not applicable



No. 1907/2006 (REACH) Printed 05.08.2019

revision 04.09.2018 (GB) Version 9.0

Flex 310 PU

	Value	Temperature	at	Method	Remark
melting point	not applicable				
Flash point	not applicable				
Vapourisation rate	not determined				
Flammable (solid)	not applicable				
Flammability (gas)	not applicable				
Ignition temperature	> 200 °C				
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	0,4 Vol-%				
Upper explosion limit	7,6 Vol-%				
Vapour pressure	< 100 hPa	20 °C			
Relative density	1,17 g/cm3	20 °C			
Vapour density	not determined				
Solubility in water					insoluble, reacts with water
Solubility/other	not determined				
Partition coefficient n- octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity dynamic	not determined				
Viscosity kinematic	not determined				
Solvent content	5,9 %				
Oxidising properties No information available.					
Explosive properties  No information available.					
9.2. Other information					

No information available.



No. 1907/2006 (REACH) Printed 05.08.2019

revision 04.09.2018 (GB) Version 9.0

Flex 310 PU

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No information available.

#### 10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

#### 10.3. Possibility of hazardous reactions

Evolution of flammable gases/vapours.

Reactions with water.

Reactions with alcohols, amines, aqueous acids and alkalies.

#### 10.4. Conditions to avoid

After contact with water:

Danger of bursting container.

## 10.5. Incompatible materials

#### Substances to avoid

Alkali (lye)

Alcohols

Amines

Acid

Water

## 10.6. Hazardous decomposition products

Nitrous gases

Hydrogen chloride (HCI)

Sulphurous oxides (SOx)

## Thermal decomposition

Remark No decomposition if used as directed.

## **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

#### Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark	
LD50 acute oral	3523 mg/kg	rat		CAS: 1330-20-7	
LD50 acute dermal	229891 mg/kg			ATE	
LC50 acute inhalation	229 mg/l (4 h)			ATE	
Skin irritation	low irritant effect - not necessary to label				
Eye irritation	low irritant - no labeling duty				
Skin sensitization	non-sensitizing				



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 04.09.2018 (GB) Version 9.0

Flex 310 PU

 Value/Validation
 Species
 Method
 Remark

 Sensitization respiratory system
 sensitizing

## Subacute Toxicity - Carcinogenicity

Subacute Toxicity - Carcinogenicity						
	Value	Species	Method	Validation		
Mutagenicity				No experimental information on genotoxicity in vitro available.		
Reproduction- Toxicity				No indications of toxic effects were observed in reproduction studies in animals.		
Carcinogenicity				No indications of carcinogenic effects are available from long-term trials.		

#### **Experiences made from practice**

Sensitization through inhalation possible.

Frequent persistent contact with the skin may cause skin irritation.

#### **Additional information**

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.

## **SECTION 12: Ecological information**

## 12.1. Toxicity

No information available.

## 12.2. Persistence and degradability

No information available.

#### 12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

#### 12.4. Mobility in soil

No information available.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Other adverse effects

#### **General regulation**

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.



No. 1907/2006 (REACH)

Printed 05.08.2019

revision 04.09.2018 (GB) Version 9.0

Flex 310 PU

## **SECTION 13: Disposal considerations**

13.1. Waste treatment methods	
Waste code No.	Name of waste
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
08 04 10	waste adhesives and sealants other than those mentioned in 08 04 09
08 04 11*	adhesive and sealant sludges containing organic solvents or other hazardous substances
08 04 12	adhesive and sealant sludges other than those mentioned in 08 04 11
15 01 02	plastic packaging
15 01 10*	packaging containing residues of or contaminated by hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

#### Recommendations for the product

Remove in accordance with local official regulations.

#### Recommendations for packaging

Dispose of according to the local waste regulations.

#### **General information**

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

## **SECTION 14: Transport information**

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	-	-	-
14.2. UN proper shipping name	-	-	-
14.3. Transport hazard class(es)	-	-	-
14.4. Packing group	-	-	-
14.5. Environmental hazards	s -	-	-

#### 14.6. Special precautions for user

Protect against moisture!

# 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable

#### **Transport/further information**

No dangerous goods as defined by the transport regulations - ADR/RID, IMDG, ICAO/IATA-DGR.

## ! SECTION 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**VOC** standard

 VOC content
 5,9 %

 VOC value
 69,3 g/L



No. 1907/2006 (REACH) Printed 05.08.2019

revision 04.09.2018 (GB) Version 9.0

Flex 310 PU

#### 15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## ! SECTION 16: Other information

#### ! Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed. For industrial use only.

#### **Further information**

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EUdirectives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.9

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312,	-?-
H332	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H373	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H413	May cause long lasting harmful effects to aquatic life.