

| Professio | nal Crimp To | ool | | | |
|--|--|--|---|--|----------------------------------|
| | | | Medium Volume | High Volume | Maintainance/ Repair |
| Terminal Type | Description | Wire type/range/Size | | | |
| | Pre-Insulated Terminal | 0.14-6 mm ² | 683-1598 or 533-279 (399-2031 German DIN) | 241-4344 or 139-704 or 267-3133 (399-2025 German DIN) | 492-9618 or 492-9624 |
| | End Splice/bootlace ferrule (Fixed Cavity) Automatic | 0.25-6mm ² 10-25mm ² 35-55mm ² 0.25-6mm ² | 683-1605 683-1614 683-1617 399-2031 | 297-2913 297-2935 297-2941 297-2991 | 492-9652 548-3185 548-3191 |
| The state of the s | Un-insulated | 0.3-2.5mm 4-10mm | 683-1608 683-1601 | 252-7658 297-2957 | 492-9630 492-9646 |
| | Open Barrell (F) Crimp | 0.1-1.5mm 0.5-6mm | 683-1620 683-1611 | 297-2979 297-2963 | 492-9668 492-9674 492-9680 |
| The same of the sa | Heat Shrink and Cool Seal | 0.5-6mm ² | 683-1642 | | 458-418 & 458-424 |
| | Coax BNC/TNC BNC Low Loss BNC. SMA, SMA N & BNC BT6A Tool Die | RG58, 59, 62, 71 RG58, 59, 62, 71 Mini RG59, RG174,179 RG213/214 VC VB VQ VR 1.0/2.3 | 683-1627 447-459 683-1623 & 683-1639 | 453-870 298-1046 298-1080 241-8380 & 298-1052 185-7734 185-7740 185-7778 185-7756 185-7762 409-3595 | 492-9719 492-9703 458-402 |
| Stripping | Tools | | | | |
| Stripping Tool | Wire Range | RS Stock No PM F | Part No Description | 1 | |

Tor - Heavy duty cable stripping tool



Ø4.5mm to Ø40mm 479-5780

4320-0763

Tool is designed to have interchangeable hooks so that one tool caters for wires with insulations up to 4.5 mm thick with diameters from 4.5 mm to 40 mm (standard hook covers 4.5 to 25 mm diameter, the large hook covers 20-40 mm diameter).



Tool will first produce a circular strip around the wire and then by simply twisting the handle produce either a spiral strip or a longitudinal strip.





| tripping Tool | Wire Range | RS Stock No | PM Part No | Description |
|------------------|---|-------------|------------|--|
| mbla Solfa | djusting cut and s | trin tool | | |
| illibia - Sell-a | 0.02mm² to 10mm² (PVC wires) | 443-0455 | 4320-0656 | Self adjusting cut and strip tool with a straight blade cassette to strip PVC insulations wires from 0.02mm² to 10mm². Featuring an insulation depth adjustment to cater for thick and thin insulations. The cassettes are easy to change without the use of any tools. |
| Pa | | | | Pt no 443-0455 is designed to work on a variety of wires by exchanging the cassettes to suite the wire type. |
| | 0.02mm² to 10mm² (PVC wires) | 443-0461 | 4320-0657 | Replacement straight blade (PVC wires) stripping cassette for Part no 443-0455. |
| | 0.1mm² to 4mm² (PTFE and other hard insulation wires) | 443-0483 | 4320-0658 | Replacement cassette to fit Pt no 443-0455 designed to strip PTFE style hard insulation wires from 0.1mm² to 4mm². |
| | 4mm² to 16mm² (PVC wires) | 479-5831 | 4320-0762 | Replacement cassette to fit Pt no 443-0455 designed to strip PVC wires from $4 mm^2$ to $16 mm^2$ |
| President | Data and signal wires 2.5mm to 11mm diameter | 479-5819 | 4320-0765 | Oden data and signal precision stripping tool featuring a fine depth adjuster and replaceable blade. To operate the tool simply squeeze the tool to open. Insert the cable and twist around the cable. |
| | | 479-5825 | 4320-0766 | Replacement blade for Pt no 479-5818. |
| E 0 | Coaxial cables from 2.5mm to 7.6mm diameter | 433-270 | 4320-0337 | Corex coaxial stripper with interchangeable cassettes to set the required strip length with a choice of two and three steps, and cable sizing "V" blocks to select cable diameter from 2.5mm up to 7.6mm diameter maximum. Kit comes complete with V blocks and an allen key for setting accurate strip depth. Choice of cassettes listed out below. |
| 19.4 | | 457-327 | 4320-0009 | Blue cassette, 2 step, jacket stripped 6.8mm. |
| | | 405-275 | 4320-0291 | Green cassette, 3 step, jacket stripped 6.0mm, braid stripped 6.0mm. |
| A Br | | 433-286 | 4320-0338 | Brown cassette, jacket stripped 7.5mm, braid stripped 3.5mm. |
| olar Cable St | tripping Tool | | | |
| San Santo St | 7mm and 8.5mm stripping length | 698-7824 | 4320-0935 | Small, light and easy to use cable stripping tool, prepare most standard solar cables without adjustment from 2.5 - 6.0mm². Fixed stripping lengt that needs no adjustment. The easily interchageable cassette makes this tool long lasting. |
| | | 698-7827 | 4320-0936 | Replacement cassette for solar stripping tool. |