

FEATURES

- Softens water without electrics or electrical displays
- Automatically set to provide correct volume of soft water
- Accurate measurement of flow rates
- Uses soft water during regeneration cycle – eliminates scale build-up
- Maintenance free parts
- Quiet operation
- Most compact, reliable and effective water softener
- Clear see-through lid to easily check salt levels
- Fast regeneration cycle
- Low salt consumption
- Low water usage per regeneration
- Suitable for all types of systems: combi, pressurised, direct high flow, unvented and megaflow

RS PRO Non-Electric Water Softener, 508 x 500 x 293 mm

RS Stock No: 195-2193



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

The powerful RS PRO NE8 needs no electrical supply. This robust and highly effective ion exchange water softener has a dual tank mechanism designed for responding to changes in water pressure. The integral service meter ensures accurate measuring of the volume of softened water passing through the unit.

The NE8 is highly recommended for its quiet operation and outstanding reliability and performance. Suitable for all types of systems: combi, pressurised, direct, high flow, vented and mega-flow.

The RS PRO NE's high-performance twin resin tanks simply go on producing a limitless supply of silky feeling soft water.

Specifications

Litres	8L
Electric	No
Mass	2 kg
Dimensions	508 x 500 x 293 mm

Compatible Installation Kits

Water Softener Installation 15 mm Valves Kit	RS stock no: 195-2200
Water Softener Installation 22 mm Valves Kit	RS stock no: 195-2203

• Our quick connect bypass included on all 3 models are designed for **ULTIMATE** convenience and saving on installation time.




- Quick release fittings to adapt to 3/4" or 1" inlet and outlet
- Integrated meter in bypass saving 5 inches of space



Non electric dimensions

	CALSOFT NE8	CALSOFT NE11
A	500mm	500mm
B	508mm	608mm
C	293mm	297mm



Installation drawing

