



## Main

Range	TeSys
Device short name	VZ
Product or component type	Additional neutral block
Performance level	High performance
Poles description	1N
Contacts type and composition	1 NO
Contact operation	Early make, late break
Product compatibility	V3 V4
Range compatibility	TeSys TeSys VARIO switch disconnecter
Network type	AC DC
Network frequency	50/60 Hz

## Complementary

Mounting location	Left Right
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	6 kV
[Ith] conventional free air thermal current	80 A
Mechanical durability	30000 cycles
Electrical durability	30000 Cycles DC-1...5 30000 cycles AC-21
Connections - terminals	Screw clamp terminals 16 mm <sup>2</sup> - flexible - with cable end Screw clamp terminals 25 mm <sup>2</sup> - solid
Tightening torque	4 N.m - on screw clamp terminals
Height	83 mm
Width	20 mm
Depth	46 mm
Net weight	0.1 kg

## Environment

Standards	IEC 60947-3
Product certifications	GL[RETURN]UL[RETURN]CSA[RETURN]UKCA
Protective treatment	TC
IP degree of protection	IP20 conforming to IEC 60529
Mechanical robustness	Vibrations 10...150 Hz (1 gn) conforming to IEC 60068-2-6 Shocks 11 ms (15 gn) conforming to IEC 60068-2-27
Ambient air temperature for operation	-20...50 °C
Fire resistance	960 °C conforming to IEC 60695-2-1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.59 cm
Package 1 Width	3.81 cm
Package 1 Length	8.89 cm
Package 1 Weight	0.09 kg
Unit Type of Package 2	S02
Number of Units in Package 2	69
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	6.28 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------