



3 PLY MEDICAL FACE MASK

EARLOOP



TOP MASK can be used for medical applications, suitable to filter germs, bacteria as well as dust and air particles.

3 PLY MEDICAL FACE MASK, EARLOOP

PRODUCT DESCRIPTION

Quality: Conforms to ASTM F2100 Level 1, EN 14683 Type IIR

Standard

Medical Face Mask, Non-sterile

Type: Material:

Polypropylene Spunbond Non-Woven, Polypropylene

Meltblown Non-Woven & Polypropylene Spunbond

Non-Woven

Color:

Outer layer (Blue), Middle layer (White),

Inner layer (White)

Design and

Feature:

3 ply disposable face mask

Storage

Condition: The face mask shall maintain its properties whilst in a

closed pack and stored in a cool dry condition


Shelf-Life: The face mask shall have a shelf life of 5 years from

the date of manufacture based on the above

storage condition

Packing

Style: 50 pcs of face masks x 40 dispensers x 1 carton



PRODUCT DIMENSION	STANDARD (mm)
Length	175 ± 5
Width	93 ± 3
Nose Wire Length	100 ± 10
Ear Loop Length	170 ± 10

Sampling Plan : ISO 2859 Single Normal

STANDARD SPECIFICATION	ASTM F2100
Classification	Level 1
Bacterial Filtration Efficiency (BFE)	≥ 99 %
Sub-micron Particulate Filtration Efficiency at 0.1 micron (PFE)	≥ 97 %
Differential Pressure	< 5.0 mm H ₂ O/cm ²
Resistance to Penetration by Synthetic Blood, minimum pressure in mmHg for pass result	80 mmHg
Flame Spread	Class 1

STANDARD SPECIFICATION	EN 14683
Classification	Type IIR
Bacterial Filtration Efficiency (BFE)	≥ 99 %
Differential Pressure	< 60 Pa/cm²
Splash Resistance Pressure	≥ 16.0 kPa
Microbial Cleanliness	≤ 30 cfu/g

A quality product manufactured by:

TOP FEEL SDN. BHD.

Lot 5090, Jalan Teratai, Batu 5, Off Jalan Meru, 41050 Klang, Selangor D. E., Malaysia If you have any enquiries on our product, please contact:

SALES & CORPORATE OFFICE

Tel: +603-3362 3098

Fax: +603-3362 5096 (Sales)

www.topglove.com



https://www.facebook.com/topglovecorp

SCAN FOR TOP MASK