

8561 B - 8566 BL

TORQUE WRENCH DREMOMETER

25-120 N·m / 18-90 lbf·ft

Use:



- > Controlled screw tightening in the range 25-120 N-m / 18-90 lbf-ft
- > For use in almost all industrial manufacturing areas

Features:

- > Classified to DIN EN ISO 6789:2003 Type II Class A, with a factory certificate. Working accuracy: +/- 3 % tolerance of scale set torque. The specification of the standard (+/- 4 %) is exceeded.
- > 1/2" square drive with ball locking device DIN 3120 - A 12.5, ISO 1174
- > Automatic short-path actuation with tactile impulse and audible signal
- > Dual scale with a scale graduation of 5 N-m and 5 lbf-ft
- > **With push-button release**

Technical advantage/Function:


- > Lightweight and robust (as housing is made of an aluminium alloy), very workshop-friendly
- > No inaccuracies whether used with both hands or held away from the handle (as for standard torque wrenches). Both the square drive and fulcrum are on an axis which ensures a high degree of user safety; can be extended to reduce the user's working load.
- > Extremely low wear attributable to reduced forces in a unique lever mechanism
- > Forged lever chain from our own quality forge
- > Maximum precision even when subjected to extreme continuous use
- > Long life cycles and tool lives
- > Easy operation - fast and safe torque tightening
- > Easy adjustment thanks to attractive adjusting button secured against loss at the end of the handle
- > Single- and double-square drive for controlled bi-directional tightening



8561-03



BR



| Type | □" | ■ | Contents | N-m | lbf-ft | lw | a | b | c | Tube | Scale | Weight | Code | No. |
|------|-----|------|---|--------|--------|-----|----|------|-----|----------|------------------|--------|---------|----------|
| BR | 1/2 | 12.5 | in plastic box with ALU extension tube | 25-120 | 18-90 | 373 | 30 | 17.5 | 462 | 8577-350 | 5 N-m / 5 lbf-ft | 2.2 | 2926989 | 8561-001 |
| B | 1/2 | 12.5 | in plastic box | 25-120 | 18-90 | 373 | 30 | 17.5 | 462 | - | 5 N-m / 5 lbf-ft | 1.5 | 7683320 | 8561-01 |
| B | 1/2 | 12.5 | in a sheet-metal case | 25-120 | 18-90 | 373 | 30 | 17.5 | 462 | - | 5 N-m / 5 lbf-ft | 2.8 | 7683830 | 8561-02 |
| B | 1/2 | 12.5 | Set mm ○ 11 13 14 17 19 22 24 ● 6 8 10 12 754-02 ← 76 + 125 + 250 mm | 25-120 | 18-90 | 373 | 30 | 17.5 | 462 | - | 5 N-m / 5 lbf-ft | 4.7 | 7684480 | 8561-03 |
| B | 1/2 | 12.5 | Set INCH ○ 7/16 1/2 9/16 19/32 5/8 11/16 3/4 25/32 13/16 7/8 15/16 1" ● 5/16 3/8 1/2" 754-02 ← 76 + 125 + 250 mm | 25-120 | 18-90 | 373 | 30 | 17.5 | 462 | - | 5 N-m / 5 lbf-ft | 5.3 | 7684990 | 8561-04 |
| BL | 1/2 | 12.5 | in plastic box | 25-120 | 18-90 | 373 | 30 | 17.5 | 462 | - | 5 N-m / 5 lbf-ft | 1.5 | 7683400 | 8566-01 |
| BL | 1/2 | 12.5 | in a sheet-metal case | 25-120 | 18-90 | 373 | 30 | 17.5 | 462 | - | 5 N-m / 5 lbf-ft | 2.8 | 7684130 | 8566-02 |
| BL | 1/2 | 12.5 | Set mm ○ 11 13 14 17 19 22 24 ● 6 8 10 12 754-02 ← 76 + 125 + 250 mm | 25-120 | 18-90 | 373 | 30 | 17.5 | 462 | - | 5 N-m / 5 lbf-ft | 4.7 | 7684640 | 8566-03 |
| BL | 1/2 | 12.5 | Set INCH ○ 7/16 1/2 9/16 19/32 5/8 11/16 3/4 25/32 13/16 7/8 15/16 1" ● 5/16 3/8 1/2" 754-02 ← 76 + 125 + 250 mm | 25-120 | 18-90 | 373 | 30 | 17.5 | 462 | - | 5 N-m / 5 lbf-ft | 5.3 | 7685100 | 8566-04 |