



Overview

Lead time	Usually in Stock
-----------	------------------



Main

Number of rack unit	2U
Battery type	Lead-acid battery
Provided equipment	User manual Battery cable Rack mounting brackets

Batteries & Runtime

Number of battery blocks per string	6
Device mounting	Rack mount
Number of battery filled slots	0
Number of battery free slots	0
Battery voltage	72 V

Physical

Colour	Black
Height	8.6 cm
Width	43.8 cm
Depth	63.2 cm
Net weight	42.5 kg
Mounting mode	Rack-mounted with kit
USB compatible	No

Conformance

Product certifications	CE[RETURN]UKCA[RETURN]EAC[RETURN]EN/IEC 62040-1
------------------------	---

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...15000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24 cm
Package 1 Width	80 cm
Package 1 Length	60 cm
Package 1 Weight	53.1 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------