

Revision Number: 005.0 Issue date: 08/21/2014

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:DB EPOXY ADH E-60HP 50 ML HARDIDH number:701986Product type:Epoxy HardenerItem number:29319_209535Restriction of Use:None identifiedRegion:United States

Company address:Contact information:Henkel CorporationTelephone: (860) 571-5100One Henkel WayMEDICAL EMERGENCY PI

One Henkel Way

Rocky Hill, Connecticut 06067

MEDICAL EMERGENCY Phone: Poison Control Center
1-877-671-4608 (toll free) or 1-303-592-1711
TRANSPORT EMERGENCY Phone: CHEMTREC

1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

DANGER: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.
MAY CAUSE AN ALLERGIC SKIN REACTION.

HAZARD CLASS	HAZARD CATEGORY
SKIN CORROSION	1B
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1





Precautionary Statements

Prevention: Do not breathe vapors, mist, or spray. Wash thoroughly after handling. Contaminated work

clothing should not be allowed out of the workplace. Wear protective gloves, eye protection,

and face protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off

immediately all contaminated clothing. IF INHALED: Remove person to fresh air and keep

comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Immediately call a poison control center or physician. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing

before reuse.

Storage: Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	4246-51-9	30 - 60
Substituted aminophenol	Proprietary	0.1 - 1
Substituted aminophenol	Proprietary	0.1 - 1

^{*} Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention.

Skin contact: Remove contaminated clothing and footwear. Immediately flush skin with

plenty of water (using soap, if available). Get medical attention. Wash clothing

before reuse. Thoroughly clean shoes before reuse.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get

medical attention.

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. Get medical attention. If vomiting occurs, prevent aspiration by keeping the patient's head

below the knees.

Symptoms: See Section 11.

IDH number: 701986

5. FIRE FIGHTING MEASURES

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: Personnel in vicinity and downwind should be evacuated. Burning produces

obnoxious and toxic fumes. Do not allow run-off from fire fighting to enter drains or water courses. Use of water may result in the formation of very

toxic aqueous solutions.

Hazardous combustion products: Ammonia. Oxides of carbon. Oxides of nitrogen. Nitric acid. Toxic fumes.

Irritating vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Ensure adequate ventilation. Wear appropriate personal protective equipment.

Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed

container for disposal.

7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling. Use only with adequate ventilation. Keep

container closed.

Storage: Keep container tightly closed and in a cool, well-ventilated place away from

incompatible materials. Keep away from heat, spark and flame. Store in

original container until ready to use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	None	None	None	None
Substituted aminophenol	None	None	None	None
Substituted aminophenol	None	None	None	None

Engineering controls: Use local exhaust ventilation if the potential for airborne exposure exists.

Respiratory protection: Use a NIOSH approved respirator if ventilation is inadequate.

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists.

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid
Color: Yellow
Odor: Mild

Odor threshold:Not available.pH:Not available.Vapor pressure:Not available.Boiling point/range:Not available.Melting point/ range:Not available.Vapor density:Not available.

Flash point: > 93 °C (> 199.4 °F) Setaflash Closed Cup

Flammable/Explosive limits - lower:
Flammable/Explosive limits - upper:
Autoignition temperature:
Evaporation rate:
Solubility in water:
Partially soluble
Partition coefficient (n-octanol/water):
Not available.
Not available.

VOC content: < 1 %; < 10 g/l Estimated

Viscosity: Not available.

Decomposition temperature: Not available.

IDH number: 701986

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: None under normal processing.

Hazardous decomposition

products:

IDH number: 701986

Ammonia. Oxides of carbon. Oxides of nitrogen. Nitric acid. Toxic fumes. Irritating vapors.

Incompatible materials: Sodium hypochlorite. Organic acids. Mineral acids. This product slowly corrodes copper,

aluminum, zinc and galvanized surfaces. Peroxides. Oxidizing agents.

Reactivity: Not available.

Conditions to avoid: Keep away from heat, ignition sources and incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation:Mists, vapors or liquid may cause severe irritation or burns.Skin contact:Causes skin burns. May cause allergic skin reaction.

Eye contact: Causes serious eye damage.

Ingestion: If ingested, severe burns of the mouth and throat may occur, as well as perforation of the

esophagus and the stomach.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	None	Corrosive
Substituted aminophenol	None	Irritant, Allergen
Substituted aminophenol	None	No Records

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
3,3'-Oxybis(ethyleneoxy)bis(propylamine)	No	No	No
Substituted aminophenol	No	No	No
Substituted aminophenol	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: It is the responsibility of the user to determine if an item is hazardous as

defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics

Leaching Procedure (TCLP) 40 CFR 261.20-24.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Amines, liquid, corrosive, n.o.s. (Polyglycol diamine)

Hazard class or division: Identification number: UN 2735 Packing group:

International Air Transportation (ICAO/IATA)

Proper shipping name: Amines, liquid, corrosive, n.o.s. (Polyglycol diamine)

Hazard class or division: Identification number: UN 2735

Packing group:

Water Transportation (IMO/IMDG)

Proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Polyglycol diamine)

Hazard class or division: Identification number: UN 2735 Packing group:

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis CERCLA/SARA Section 311/312: Immediate Health CERCLA/SARA Section 313: None above reporting de minimis

California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Rena Petrides, Regulatory Affairs Specialist

Issue date: 08/21/2014

IDH number: 701986 Product name: DB EPOXY ADH E-60HP 50 ML HARD **DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

IDH number: 701986 Product name: DB EPOXY ADH E-60HP 50 ML HARD