

Datasheet

RS PRO 4CORE INDIVIDUAL LAPPED SCREEN CABLE 50M

Stock No: 2075322




Technical Specifications:

Conductor	Bare Copper	Filler	-
Cores Number	4C	Cabling	Yes
Size(mm ²)	0.078	Overall Mylar Spiral	PET Mylar
Construction(±0.008mm)	10/0.10	Jacket Material	PVC
Stranded Dia.(mm)	0.36	Jacket Color	Grey (RAL7001)
Insulation Material	PE	Ave Thickness(mm)	0.80
Insulation Color	YL,BU,RD,WH	Min Thickness(mm)	0.64
Ave Thickness(mm)	0.40	Outer Dia(±0.15mm)	5.20
Min Thickness(mm)	0.32		
Insulation Dia.(±0.10mm)	1.20		
Spiral (on each core)	Bare Copper		
Construction(±0.008mm)	36/0.10BC		

Features & Benefits:

- Operating temperature: -20~+60 °C
- Conductor resistance(20°C Ω/km): 237max.
- Insulation DC Resistance(20°C MΩ*Km): 200min.
- Operating voltage: 30 V

Cross Section drawings



Cable Marking: RS PRO 4 Core×0.078mm²
Screened Cable 30V

Applications:

This multicore microphone cable can be soldered to standard jack and XLR connectors to make custom audio cables that can connect microphones and instruments to mixers or amplifiers. This high-quality audio cable is suitable for; Live stages and theatres
Professional studio setups
Hobbyist and custom audio setups