

DOCTOR-CHARGE55



- Professional, multi-functional electronic battery charger (battery manager) for WET, GEL, AGM, MF, PbCa, EFB, Li 6V/12V/24V batteries. With LCD screen
- Automatic charging and trickle charging in Pulse Tronic based on the technology of the selected battery. Automatic recognition of battery type (AUTO mode)
- Stable power supply unit for diagnostic activities (BSU), during batetry changes (SUPPLY) and to keep showrooms; RECOVERY function, to recover sulphated or very flat batteries and EQUALIZATION function, to recover optimal functionality with periodic regeneration
- Advanced functions: BOOST for rapid charging; COLD for charging and trickle of batteries at low temperatures; TEST alternator, cranking and charging status of the battery; Cranking aid
- Cable elongation compensation function; Integrated PFC (Power Factor Correction) for reduced absorption and greater stability of the charging current
- Cable with clamps

Description

Multifunctional, electronic battery charger (BATTERY MANAGER) for complete maintenance of WET, GEL, AGM, MF, PbCa, EFB, Li 6V/12V/24V batteries and for support activities in interventions, including diagnostics, on vehicles carried out in workshops, body shops and dealers.

The Pulse Tronic technology guarantees optimal battery charging over 8 phases.

| Technical Data | |
|---------------------------------|------------------|
| Single Phase Mains Voltage | 230 V |
| Mains frequency | 50/ 60Hz |
| Charging absorbed power | 610 W |
| Charging voltage | 6/ 12/ 24 V |
| Effective charging current | 45/ 45/ 23A |
| Rated charge curr. EN60335-2-29 | 40/ 40/ 20A |
| Start current 1V/C EN60335-2-29 | 40 (BOOST) A |
| Start current 1V/C EN60335-2-29 | 50 A |
| Min. rated reference capacity | 10 Ah |
| Max. rated reference capacity | 600 Ah |
| Protection degree | IP33 |
| Dimensions | 9.2 x 20 x 33 cm |
| Weight | 4 kg |