# NSYPLM86G

Wall mounted polyester enclosure, Thalassa PLM, plain door, 847x636x300mm, IP66, IK10, RAL 7035





#### Main

Range	Thalassa
Product name	Thalassa PLM
Device short name	PLM
Enclosure type	Multi-purpose
Category	Compact enclosure
Nominal height	847 mm
Nominal width	636 mm
Nominal depth	300 mm
Enclosure mounting	Wall mounted
Device composition	1 body
	1 door
	2 lock
Door type	Plain
Lock type	3 mm double-bar lock

#### Complementary

Number of locks	2	
Mounting plate description	Without mounting plate	
Accessibility for operation	Front	
Removable parts	Door by hinges	
Material	Polyester reinforced with fibreglass	
Colour	Grey (RAL 7035)	
Standards	IEC 62208 NEMA classification 4X NEMA classification 13	
Product certifications	UL	
Electrical insulation class	Class II	

### Environment

IP degree of protection	IP66 conforming to IEC 60529	
IK degree of protection	IK10 conforming to IEC 62262	
Fire resistance	960 °C conforming to IEC 62208	
Ambient air temperature for operation	-4080 °C	

### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	33.0 cm	
Package 1 Width	66.5 cm	
Package 1 Length	92.5 cm	
Package 1 Weight	19.341 kg	

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☐ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile