Cartridge Fuse





RoHS Compliant

Application

- · PV combiner/ junction boxes
- Inverters
- · Battery Charge Controllers

Features

- 1000 / 1100 VDC, 10x38 mm PV fuse-link with glass-fiber
- · Rated Current: 1-32 A
- Breaking Capacity: 30 kA @ 1100 VDC (1-32 A)
- Self Certified: 50 kA @ 1100 VDC (1-20A)
- · Time Constant: 1-3 ms
- · Special design with silver plated caps for high-power PV applications

Agency Information

- Comply to: UL 248-19 (File: E490190)
 Approvals: IEC 60269-6/GBT 13539.6
- · Manufactured under IATF 16949 quality system


Specifications

	Datad	Rated Ampere Breaking Cold Resist urrent Code Capacity (mΩ)	Brooking	Cold Posistanos	I2t (A2s)		Dissipation (W)	
Part Number	Current			Pre- Arcing	Total	80% In	100% In	
MP011847	15A	2150	30 kA@ 1100V DC	6.15 to 9.23	300	1650	1.6	2.2
MP011848	20A	2200		3.90 to 5.85	400	2200	2.1	2.9
MP011849	25A	2250		2.92 to 4.38	500	2750	2.7	3.6
MP011850	30A	2300		2.21 to 3.33	600	3300	3.2	4.3

Time Vs Current Characteristic

Standard	UL			Requirements / Result		
Rated Current	100 %	135 %	200 %	100 %	113 %	145 %
1-32 A	Temperature Stabilization	<1 h	<4 min	Temperature Stabilization	>1 h	<1 h

Dimensions



Dimensions : Millimetres


Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro



Cartridge Fuse



Time Current Curve (reference)



Part Number Table

Description	Part Number	
Cartridge Fuse, 15A, 10mm x 38mm, 1100V	MP011847	
Cartridge Fuse, 20A, 10mm x 38mm, 1100V	MP011848	
Cartridge Fuse, 25A, 10mm x 38mm, 1100V	MP011849	
Cartridge Fuse, 30A, 10mm x 38mm, 1100V	MP011850	

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro



06/06/23 V1.0