Relay

multicomp



Coil Data

Contact Data

Contact Material Contact Rating : Ag alloy : 1 form C (SPDT): 10A 120V AC / 24V DC, 6A 250V AC TV-5

Max. Switching Voltage	: 250V AC / 24V DC
Max. Switching Current	: 10A
Max. Switching Power	: 1,800VA, 360mW
Min. Switching Load	: 5V DC, 100mA
Contact Resistance	: Max. 50mΩ (6V DC 1A)

Life

Electrical	: 100,000 operations
Mechanical	: 10,000,000 operations

General Data

Insulation Resistance	: Min. 1,000mW 500V DC
Dielectric Strength	: 750V AC, 1 min. between open contacts 1,500V AC, I min. between coil and contacts
Operate Time	: Max. 10ms
Release Time	: Max. 5ms
Operate Temperature	: -30 ℃ to +85 ℃

: 360mW

Shock Resistance

Endurance	: 1,000m/s ²		
Mis-operation	: 100m/s ²		

Vibration Resistance

Endurance	: 10 to 55Hz, 1.5mm double amplitude
Mis-operation	: 10 to 50Hz, 1.5mm double amplitude
Humidity	: 35% to 95% RH, +40 ℃
Weight	: Approximately 10g

www.element14.com www.farnell.com www.newark.com





Coil Data Chart

Nominal Voltage V DC	Coil Resistance W ±10%	Operate Voltage ≤V DC	Release Voltage ≥V DC	Coil Power mW	Contact Form	Part Number
12	400	8.4	1.2	360	360 1 Form C M	MC25138
24	1,600	16.8	2.4			MC25139

Dimensions



Dimensions : Millimetres

Characteristic Chart Data



www.element14.com www.farnell.com www.newark.com

Coil Temperature Rise







Characteristic Chart Data





Part Number Table

Description	Part Number	
Relay	MC25138	
	MC25139	

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. ® Premier Farnell pic 2012.

www.element14.com www.farnell.com www.newark.com

