


RoHS  
Compliant



## Specifications

Connector Type : Ferrule  
Contact Material : Copper  
Contact Plating : Tin

## Diagram



## Part Number Table

Description	Size (mm <sup>2</sup> )	AWG	Colour	Dimensions (mm)						Part Number
				L-1	L-2	D-1	S-1	D-2	S-2	
Insulated Wire Ferrules	0.5	20	Orange	11.5	6	1.1	0.15	2.5	0.25	SPC4473
				13.5	8					SPC4474
				15.5	10					SPC4475
	0.75	20	White	12	6	1.3	0.15	2.8	0.25	SPC4476
				14	8					SPC4477
				16	10					SPC4478
				18	12					SPC4479
	1	18	Yellow	12.5	6	1.5	0.15	3	0.3	SPC4480
				14.5	8					SPC4481
				16.5	10					SPC4482
				18.5	12					SPC4483
	1.5	16	Red	12.5	6	1.8	0.15	3.4	0.3	SPC4484
				14.5	8					SPC4485
				16.5	10					SPC4486
				18.5	12					SPC4487
				24.5	18					SPC4488
	2.5	14	Blue	15	8	2.3	0.15	4.2	0.3	SPC4489
				19	12					SPC4490
				25	18					SPC4491

# Insulated Wire Ferrules

Description	Size (mm <sup>2</sup> )	AWG	Colour	Dimensions (mm)						Part Number
				L-1	L-2	D-1	S-1	D-2	S-2	
Insulated Wire Ferrules	4	12	Grey	17.5	10	2.9	0.2	4.8	0.3	SPC4492
				20	12					SPC4493
				26	18					SPC4494
	6	10	Black	20	12	3.6	0.2	6.2	0.3	SPC4495
				25	18					SPC4496
	10	8	Ivory	21	12	4.6	0.2	7.5	0.3	SPC4497
				27	18					SPC4498
	16	6	Green	23	12	6	0.2	8.8	0.4	SPC4499
				29	18					SPC4500
	25	4	Brown	29	16	7.5	0.2	11	0.5	SPC4501
				31	18					SPC4502
				35	22					SPC4503
	0.5	20	White	11.5	6	1.1	0.15	2.5	0.25	SPC4504
				13.5	8					SPC4505
				15.5	10					SPC4506
	0.75	20	Grey	12	6	1.3	0.15	2.8	0.25	SPC4507
				14	8					SPC4508
				16	10					SPC4509
				18	12					SPC4510
	1	18	Red	12.5	6	1.5	0.15	3	0.3	SPC4511
				14.5	8					SPC4512
				16.5	10					SPC4513
				18.5	12					SPC4514
	1.5	16	Black	12.5	6	1.8	0.15	3.4	0.3	SPC4515
				14.5	8					SPC4516
				16.5	10					SPC4517
				18.5	12					SPC4518
				24.5	18					SPC4519
	2.5	14	Blue	15	8	2.3	0.15	4.2	0.3	SPC4520
				19	12					SPC4521
25				18	SPC4522					
4	12	Grey	17.5	10	2.9	0.2	4.8	0.3	SPC4523	
			20	12					SPC4524	
			26	18					SPC4525	
6	10	Yellow	20	12	3.6	0.2	6.2	0.3	SPC4526	
			25	18					SPC4527	

Description	Size (mm <sup>2</sup> )	AWG	Colour	Dimensions (mm)						Part Number
				L-1	L-2	D-1	S-1	D-2	S-2	
Insulated Wire Ferrules	10	8	Red	21	12	4.6	0.2	7.5	0.3	SPC4528
				27	18					SPC4529
	16	6	Blue	23	12	6	0.2	8.8	0.4	SPC4530
				29	18					SPC4531
	25	4	Yellow	29	16	7.5	0.2	11	0.5	SPC4532
				31	18					SPC4533
				35	22					SPC4534

**Important Notice :** This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.