# MUR36030

Socket-outlet, Mureva Styl, 2P + E with shutters, pin earth, 16A, 250V, surface, grey





# Main Range Mureva Styl Product or component type Socket-outlet Device presentation Complete product Outlet poles configuration 2P + E Outlet standard Pin earth

French

Grey (RAL 7016)

$\sim$					
Co	mn	lem	าer	ารล	rv/

Device mounting	Surface
Socket number	1
Rated current	16 A
[Ue] rated operational voltage	250 V AC
Condition of use	Indoor/outdoor
Material	Brass PP (polypropylene) PC (polycarbonate)
Fixing mode	By screws
Cable entry	Easy valve access diameter: 612 mm
Height	76 mm
Width	76 mm
Depth	64 mm
Chemical and detergent products resistance	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

Outlet standard description
Outlet standard

Colour tint

### Environment

Quality labels	NF
IP degree of protection	IP55
IK degree of protection	IK08
Flame retardance	Self-extinguishing 650 °C conforming to IEC 60695-2-1
Ambient air temperature for operation	-540 °C
Ambient air temperature for storage	-2555 °C

# Packing Units

PCE
1
7.600 cm
6.500 cm
7.600 cm
133.000 g
BB1
10
8.000 cm
16.000 cm
39.500 cm
1.418 kg
S04
60
30.000 cm
40.000 cm
60.000 cm
9.336 kg

## Offer Sustainability

Office Gastamability		
Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	€Yes	
Environmental Disclosure	Product Environmental Profile	