



Benefits

- Compact and powerful
- Long lifespan
- Up to 50% energy savings compared to CFL

Application



Model	Item Description	W	PF	lm	lm/W	CRI	Beam	Life	Single Box (LxWxH)mm	Outer Box (LxWxH)mm	Packing Qty (PCS/CTN)
YTG95Z1-G95-12W-E27	CLSV1 G95 12W E27 3000K	12	0.5	1200	100	80	240°	20000	98*98*150	515*412*170	20
YTG95Z1-G95-12W-E27	CLSV1 G95 12W E27 4000K	12	0.5	1200	100	80	240°	20000	98*98*150	515*412*170	20
YTG95Z1-G95-12W-E27	CLSV1 G95 12W E27 6500K	12	0.5	1200	100	80	240°	20000	98*98*150	515*412*170	20
YTG120Z1-G120-15W-E27	CLSV1 G120 15W E27 4000K	15	0.5	1500	100	80	240°	20000	124*124*170	645*516*190	20
YTG120Z1-G120-15W-E27	CLSV1 G120 15W E27 6500K	15	0.5	1500	100	80	240°	20000	124*124*170	645*516*190	20

Application Conditions	
IP	IP20
Operating Temperature	-20~40°C
Application Temperature	25°C
Storage Environment	-25~50°C

Mechanical Properties	
Optical Material	PC
Housing Material	PBT
Finishing Colour	White

Electrical Supply	
Frequency (Hz)	50/60
Voltage (V)	220-240
AC/DC	AC

Dimensional Drawing

