



Specifications

Conductor Material	: Stranded Bare Copper
Insulation Material	: 89A TPE(Halogen Free)
Rated Temperature	: 105°C
Rated Voltage	: 600V
Safety Certifications	: UL29328

Specification Table

Part Number	Construction Strands/ Strand Size (mm)	Conductor Diameter (mm)	Insulation Diameter (mm)	AWG	Conductor
MP011186	41/0.16 ±0.008	6.4 ±0.3	6.4 ±0.3	18	2C
MP011187	41/0.16 ±0.008	6.4 ±0.3	6.4 ±0.3	18	2C
MP011188	35/0.254 ±0.008	8.3 ±0.3	8.3 ±0.3	16	3C
MP011189	35/0.254 ±0.008	8.3 ±0.3	8.3 ±0.3	16	3C

Part Number Table

Description	Insulation Colour	Length (ft.)	Part Number
Halogen Free power cable, UL20328, 2C	Black/White	50	MP011186
	Black/White	100	MP011187
Halogen Free power cable, UL20328, 3C	Black/White/Green	50	MP011188
	Black/White/Green	100	MP011189

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.