A9XPH424

Acti 9 - comb busbar - 3L+N - 18 mm pitch - 24 modules - 100 A





| Range | Acti9 |
|------------------------------------|----------------------|
| Product or component type | Comb busbar |
| Mounting mode | Horizontal |
| Accessory / separate part category | Connection accessory |
| Lines description | 3L + N |
| Length in 18 mm modules | 24 |



Complementary

| o in promortiary | | |
|--------------------------------|--|--|
| Number of ways | 6 ways N + 3 L | |
| Poles configuration for 1 way | 1 x 3P + N | |
| | 1 x 4P | |
| Connection pitch | 18 mm | |
| Connector type | Tooth | |
| Distance between way | 72 mm | |
| Marking | N L1 L2 L3 | |
| Insulation | Insulated | |
| Device presentation | Cuttable | |
| [le] rated operational current | 100 A at 40 °C | |
| [Ue] rated operational voltage | 415 V AC | |
| [Ui] rated insulation voltage | 500 V AC conforming to IEC 61439-2 | |
| Mounting location | Top or bottom on tunnel type terminals | |
| | Top or bottom on double terminal | |
| 9 mm pitches | 48 | |
| Width | 430 mm | |
| Colour | White (RAL 9003) | |
| Range compatibility | Acti 9 Acti9 iC60 | |
| | Acti 9 Acti9 iK60 | |
| | Acti 9 Acti9 iID | |
| | Acti 9 Acti9 iID K | |
| | Acti 9 Acti9 iSW | |
| | Acti 9 Acti9 iSW-NA | |
| | Multi9 Multi9 C60 | |
| | | |

Environment

| Standards | IEC 60947-7-1 IEC 61439-2 | |
|-------------------------|---|--|
| Fire resistance | 960 °C (30 s) conforming to IEC 60695-2-1 | |
| Pollution degree | 3 conforming to IEC 60947-7-1 | |
| IP degree of protection | IP20 with end-pieces and tooth covers | |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|-----------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 5.600 cm |
| Package 1 Width | 8.400 cm |
| Package 1 Length | 46.600 cm |
| Package 1 Weight | 289.000 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 5 |
| Package 2 Height | 5.600 cm |
| Package 2 Width | 8.400 cm |
| Package 2 Length | 46.600 cm |
| Package 2 Weight | 1.546 kg |
| Unit Type of Package 3 | S04 |
| Number of Units in Package 3 | 35 |
| Package 3 Height | 30.000 cm |
| Package 3 Width | 40.000 cm |
| Package 3 Length | 60.000 cm |
| Package 3 Weight | 11.790 kg |
| | |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|----------------------------|---|
| REACh Regulation | REACh Declaration |
| REACh free of SVHC | Yes |
| EU RoHS Directive | Compliant EEU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | ☐ China RoHS Declaration |
| RoHS exemption information | ₫Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| Warranty | 18 months |
|----------|-----------|
|----------|-----------|