

FEATURES

- Low cost
- Excellent insulation properties
- Flexible
- Stable, robust and durable
- Oil resistant

RS PRO 3 Core 2.5 mm² Mains Power Cable, Orange Polyvinyl Chloride PVC Sheath 100m, 20 A 500 V, 3183Y H05VV-F

RS Stock No.: 491-914



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



Product Description

From RS PRO a high-quality BASEC approved medium duty H05VV-F harmonised flexible mains power cable with PVC insulation and a PVC jacket. This flexible cable has a voltage rating of 300 to 500 V and is designed for use in medium duty domestic and office applications.

General Specifications

Туре	3183Y
Harmonised Code	H05VV-F
Sheath Material	Polyvinyl Chloride PVC
Sheath Colour	Orange
Applications	Computer and office equipment, Kitchen appliances such as toasters, Household appliances such as vacuum cleaners and washing machines, Radios and music centres, Table lamps and floor lamps, Hair dryers, Electrical cooking or heating apparatus

Electrical Specifications

Current Rating	20A
Voltage Rating	500V
Insulation Material	PVC
Conductor Material	Copper
Conductor Resistance	7.98 Ω/km



Mechanical Specifications

Length	100m
Cross Sectional Area	2.5 mm ²
American Wire Gauge	13AWG
Outer Diameter	11.4mm
Number of Cores	3
Number of Strands	48
Size of Strands	0.22mm
Core Strands	48/0.22mm
Conductor Strand Type	Stranded

Operation Environment Specifications

Operating Temperature Range	-15°C to +70°C
Minimum Operating Temperature	-15°C
Maximum Operating Temperature	+70°C

Approvals

Compliance/Certifications	2011/65/EU and 2015/863
Standards Met	BS EN 50525, BS6500, CENELEC HD21.5 and BASEC, BS EN 50525-2-11





