

No. 1907/2006 (REACH)
Printed 05.08.2019

revision 19.06.2019 (GB) Version 8.8

Mould Release Agent Wax P 500

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product Mould Release Agent Wax P 500

Code-Nr. 106045

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

Release Agents

1.3. Details of the supplier of the safety data sheet

**Distributor** WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

Phone: +49(0)251 / 9322 - 0, Fax: +49(0)251 / 9322 - 244

E-Mail: msds@weicon.de Internet: www.weicon.de

Advice Produktsicherheit / Product-Safety-Department

Phone : +49(0)251 / 9322 - 0 Fax : +49(0)251 / 9322 - 244 E-mail (competent person):

msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:

++44 1865 407333 (English)

TRANSPORT EMERGENCY CONTACT - UK, UAE, South

Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer WEICON GmbH & Co. KG

Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):

Tel: ++49 69 222 25285 (Deutsch, Englisch)

#### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard Hazard Statements Classification procedure categories

 Flam. Sol. 1
 H228

 Skin Irrit. 2
 H315

 STOT SE 3
 H336

 Aquatic Chronic 3
 H412

**Hazard Statements** 

H228 Flammable solid.H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 19.06.2019 (GB) Version 8.8

Mould Release Agent Wax P 500

H412

Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]





GHS02

GHS07

#### Signal word

Danger

#### **Hazard Statements**

H228 Flammable solid.H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

## **Precautionary Statements**

P102	Keep out of reach of children.
P210 P241 P261 P271 P273	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical/ventilating/lighting/equipment. Avoid breathing vapours/spray. Use only outdoors or in a well-ventilated area. Avoid release to the environment.
P301 + P310 P302 + P352 P304 + P340 P312 P331 P332 + P313 P362 + P364 P370 + P378	IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use dry sand to extinguish.
P403 + P233 P405	Store in a well-ventilated place. Keep container tightly closed. Store locked up.

## Hazardous ingredients for labeling

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics, Solvent naphtha (petroleum), light arom. (NOTA P)

Dispose of contents/container to hazardous or special waste collection point.

## Supplemental Hazard information (EU)

Repeated exposure may cause skin dryness or cracking.

## 2.3. Other hazards

P501

## Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.



No. 1907/2006 (REACH) Printed 05.08.2019

revision 19.06.2019 (GB) Version 8.8

Mould Release Agent Wax P 500

## ! SECTION 3: Composition/ information on ingredients

#### 3.1. Substances

not applicable

#### 3.2. Mixtures

#### ! Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]		
64742-49-0	927-241-2	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	50 < 100	Flam. Liq. 3, H226 / Asp. Tox. 1, H304 / STOT SE 3, H336 / Aquatic Chronic 3, H412		
64742-95-6	265-199-0	Solvent naphtha (petroleum), light arom. (NOTA P)	10 < 25	Asp. Tox. 1, H304 / STOT SE 3, H335, H336 / Aquatic Chronic 2, H411 / , EUH066 / /		
REACH						
CAS No	Name			REACH registration number		
64742-49-0	Hydrocarbon	s, C9-C10, n-alkanes, isoalkanes, cyclics, <2% arc	matics	01-2119471843-32		
64742-95-6	Solvent naph	ntha (petroleum), light arom. (NOTA P)	01-2119455851-35			
Additional a						

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### **General information**

Remove contaminated soaked clothing immediately.

## In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

## In case of skin contact

In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

## In case of eye contact

In case of contact with eyes rinsing with plenty of lukewarm water carefully and seek for medical treatment.

## In case of ingestion

Do not induce vomiting.

Call for a doctor immediately.

# 4.2. Most important symptoms and effects, both acute and delayed Physician's information / possible symptoms

Cyanosis

Acidosis

Shortness of breath

vomiting

Headache

Confusion

## 4.3. Indication of any immediate medical attention and special treatment needed

No information available.



No. 1907/2006 (REACH) Printed 05.08.2019

revision 19.06.2019 (GB) Version 8.8

Mould Release Agent Wax P 500

## **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media Suitable extinguishing media

Alcohol-resistant foam
Dry fire-extinguishing substance
Carbon dioxide
sand

#### Unsuitable extinguishing media

water

## 5.2. Special hazards arising from the substance or mixture

May lead to formation of explosive/easily ignitable vapour air mixtures.

In case of fire formation of dangerous gases possible.

Carbon monoxide (CO)

Carbon dioxide (CO2)

#### 5.3. Advice for firefighters

## Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

#### **Additional information**

Burns down under strong soot production.

Cool endangered containers with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Ensure adequate ventilation.

Keep people away and stay on the upwind side.

Use personal protective clothing.

Keep away sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.

#### 6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains or bodies of water..

Do not discharge into the subsoil/soil.

## 6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

Send in suitable containers for recovery or disposal.

After taking up the material dispose according to regulation.

#### 6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13

Personal protection equipment: see section 8



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 19.06.2019 (GB) Version 8.8

Mould Release Agent Wax P 500

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

#### Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

#### General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

#### Hygiene measures

At work do not eat, drink, smoke or take drugs.

Remove soiled or soaked clothing immediately.

Wash hands before breaks and after work.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Vapours can form an explosive mixture with air.

Take precautionary measures against static discharges.

Use explosion-proof equipment / fittings and non-sparking tools.

## 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep in closed original container.

## Advice on storage compatibility

Do not store together with animal feedstuffs.

Do not store together with food.

Do not store together with oxidizing agents.

#### Further information on storage conditions

Keep container tightly closed and store at cool and aired place.

Protect from heat and direct solar radiation.

Storage temperature between 10°C to 30°C (=50°F to 86°F).

Store in a dry place.

Do not keep at temperatures above 10°C.

Do not keep at temperatures above 30°C.

## 7.3. Specific end use(s)

## Recommendation(s) for intended use

See section 1.2

#### ! SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

**DNEL-/PNEC-values** 

**DNEL** worker

CAS No	Substance name	Value	Code	Remark
64742-49-0	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	300 mg/kg bw/day	DNEL long-term dermal (local)	
		1500 mg/m3	DNEL acute inhalative (local)	

#### ! Additional advice

The statutory local and national regulations have to be observed.



No. 1907/2006 (REACH) Printed 05.08.2019

revision 19.06.2019 (GB) Version 8.8

Mould Release Agent Wax P 500

## 8.2. Exposure controls

## Respiratory protection

If ventilation insufficient, wear respiratory protection.

Short term: filter apparatus, Filter A/P2

#### **Hand protection**

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Gloves (solvent-resistant)

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]:: Nitrile rubber; 0,4mm; 480min;60min.

#### Eye protection

tightly fitting goggles

## Other protection measures

protective clothing

#### Appropriate engineering controls

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

## **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Appearance<br/>pastyColour<br/>whitishOdour<br/>characteristic

# Odour threshold not determined

## Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	> 140 °C			DIN 53171	
melting point	not determined				
Flash point	> 24 °C			closed cup	
Vapourisation rate	not determined				
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	200 °C			DIN 51794	
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	0,6 Vol-%				
Upper explosion limit	7 Vol-%				



No. 1907/2006 (REACH) Printed 05.08.2019

revision 19.06.2019 (GB) Version 8.8

## Mould Release Agent Wax P 500

	Value	Temperature	at	Method	Remark
Vapour pressure	5 hPa	20 °C			
Relative density	0,8 g/cm3	20 °C		ISO 2811	
Vapour density	not determined				
Solubility in water	< 0,1 g/l	20 °C			
Solubility/other	not determined				
Partition coefficient n- octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity dynamic	not determined				
Viscosity kinematic	not determined				
Solvent separation test	< 3 %				

## **Oxidising properties**

No information available.

## **Explosive properties**

The product is considered non-explosive; nevertheless explosive vapour/air mixtures can be generated.

#### 9.2. Other information

No information available.

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

No information available.

#### 10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

## 10.3. Possibility of hazardous reactions

Reactions with oxidising agents.

## 10.4. Conditions to avoid

Keep away from heat.

# 10.5. Incompatible materials

Substances to avoid

oxidising agent

## 10.6. Hazardous decomposition products

Smoke

Carbon monoxide and carbon dioxide.

Hydrocarbons



No. 1907/2006 (REACH) Printed 05.08.2019

revision 19.06.2019 (GB) Version 8.8

Mould Release Agent Wax P 500

## Thermal decomposition

Remark No decomposition if used as directed.

## ! SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

#### Acute toxicity/Irritation/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	3492 mg/kg	rat	OECD 401	CAS: 64742-95-6
LD50 acute dermal	> 3160 mg/kg	rabbit	OECD 402	CAS: 64742-95-6
LC50 acute inhalation	> 5,6 mg/l (4 h)	rat	Aerosol	CAS: 64742-49-0
Skin irritation	irritant			
Eye irritation	low irritant - no labeling duty			
Skin sensitization	non-sensitizing			

## **Subacute Toxicity - Carcinogenicity**

	Value	Species	Method	Validation
Mutagenicity				No experimental information on genotoxicity in vitro available.
Reproduction- Toxicity				No indications of toxic effects were observed in reproduction studies in animals.
Carcinogenicity				No indications of carcinogenic effects are available from long-term trials.

## Specific target organ toxicity (single exposure)

May cause drowsiness or dizziness.

## Experiences made from practice

Often and long skin contact may cause degreasing and desiccation of the skin which may caus skin irritation.

Experiences at humans: may cause hypersensitivity reactions on skin in case of persons suffering from hypersensitivity.

## **Additional information**

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.



No. 1907/2006 (REACH) Printed 05.08.2019

revision 19.06.2019 (GB) Version 8.8

Mould Release Agent Wax P 500

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

## **Ecotoxicological effects**

	Value	Species	Method	Validation	
Fish	LC50 9,2 mg/l (96 h)	Oncorhynchus aquabonita	OECD 203	CAS: 64742-95-6	
Daphnia	EC50 3,2 mg/l (48 h)	Daphnia magna	OECD 202	CAS: 64742-95-6	
Algae	EC50 2,9 mg/l (72 h)	Pseudokirchneriella subcapitata	OECD 201	CAS: 64742-95-6	

#### 12.2. Persistence and degradability

No information available.

#### 12.3. Bioaccumulative potential

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

#### 12.4. Mobility in soil

No information available.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Other adverse effects

## **General regulation**

Harmful to aquatic life with long lasting effects.

Even in the event of low quantities penetration into the underground drinking water is contaminated.

Toxic to fishes

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

## Recommendations for the product

Remove in accordance with local official regulations.

Dispose of as hazardous waste.

## Recommendations for packaging

Dispose of according to the local waste regulations.

Packaging that cannot be cleaned should be disposed of like the product.

### **General information**

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

## **SECTION 14: Transport information**

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	3175	3175	3175



No. 1907/2006 (REACH)
Printed 05.08.2019

revision 19.06.2019 (GB) Version 8.8

## Mould Release Agent Wax P 500

	ADR/RID	IMDG	IATA-DGR
14.2. UN proper shipping name	SOLIDS CONTAINING FLAMMABLE LIQUID, N.O. S. (Naphtha (petroleum), hydrotreated heavy)	SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Naphtha (petroleum), hydrotreated heavy)	Solids containing flammable liquid, n.o.s. (Naphtha (petroleum), hydrotreated heavy)
14.3. Transport hazard class(es)	4.1	4.1	4.1
14.4. Packing group	II	II	II
14.5. Environmental hazards	No	No	No

## 14.6. Special precautions for user

No information available.

# 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

## Land and inland navigation transport ADR/RID

Hazard label(s) 4.1 tunnel restriction code E Classification code F1

#### Transport/further information

Marine pollutant: NO

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**VOC** standard

VOC content 0 % 15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## ! SECTION 16: Other information

#### ! Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

#### **Further information**

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EUdirectives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.7

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H335,	-?-
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.