



### Main

Range	Vivace
Device short name	KB31
Product or component type	Data socket with shutter
Device application	Communication
Device presentation	Complete mechanism
Cover frame colour tint	White

### Complementary

Communication network category	6
Number of gangs	1 gang
Tightening torque	0.4 N.m
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Width	86 mm
Height	86 mm
Projecting depth	8 mm
Embedding depth	35 mm

### Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use
Standards	FCC

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	83.7 g
Package 1 Height	8.6 cm
Package 1 Width	5.0 cm
Package 1 Length	8.6 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	907.0 g
Package 2 Height	15.0 cm
Package 2 Width	19.0 cm
Package 2 Length	10.0 cm
Unit Type of Package 3	CAR

Number of Units in Package 3	100
Package 3 Weight	8620.0 g
Package 3 Height	315.0 mm
Package 3 Width	500.0 mm
Package 3 Length	500.0 mm

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>