# "HIT" INDUSTRIAL TOOLS - Japan

# Sleeve

## NO. S 1-16 "HIT" SWAGING TOOL

Multi-compression hand swager with or without cable cutters. Durable jaws are made from forged alloy steel with special heat treated and hardened.

Item No.	Model	Wire Rope Dia. For	Cutting	Lgth	Price
	No.	Swagging & Cutting	Capacity	(mm)	(pc)
001-16-CT350	CT350/3	1/16", 3/32", 1/8"	w/o cutter	350	
001-16-CT350C	CT350/3C	1/16", 3/32", 1/8"	1/8"	350	
001-16-CT600	CT600/5	1/16", 3/32", 1/8", 5/32", 3/16"	w/o cutter	600	
001-16-CT600C	CT600/5C	1/16", 3/32", 1/8", 5/32", 3/16"	1/4"	600	
001-16-CT750	CT750/3	5/32", 1/4", 5/16"	w/o cutter	750	
001-16-CT750C	CT750/3C	5/32", 1/4", 5/16"	5/16"	750	
001-16-CT900	CT900	3/8"	w/o cutter	900	

Packing: 1 pc per box



### NO. S 1-18 "HIT" HEAVY DUTY STEEL STRAP CUTTER

Drop-forged high special alloy tool steel jaws with heat-treated.

Shear-cut blades give clean, smooth and easy cut, excellent for pallets, loading and unloading freight cars, trucks and machines.

SS600-SS includes hammer function (Sliding Striker)



Item No.	Length	Steel Strap	Wt	Packing	Price
	(mm)	(mm)	(kg)	(pcs/box)	(pc)
001-18-SS200	240	32 x 0.9	0.3	6	
001-18-SS450	450	50 x 1.2	1.4	1	
001-18-SS600	600	50 x 1.3	2.7	1	
001-18-SS600SS	600	50 x 1.3	3.0	1	
001-18-SSBN600	-18-SSBN600 Spare bolt & nut for SS-600				

### NO. S 1-19 "HIT" ADJUSTABLE WRENCH

All HIT Adjustable Wrenches exceed JAPAN JIS Standard and U.S.A. Federal Specification No GGG-W-631b, Type I Heavy-Duty. Made of all drop-forged steel, with chrome plated finish.



**SS600-SS** 

**CHROME FINISH** 

Item No.	Length	Capacity	Wt	Packing	Price
	(mm)	(mm)	(g)	(pcs/box)	(pc)
001-19-SM100	100 ( 4")	14	46	6	
001-19-SM150	150 ( 6")	21	110	6	
001-19-SM200	200 ( 8")	25	230	6	
001-19-SM250	250 (10")	30	390	6	
001-19-SM300	300 (12")	35	590	6	
001-19-SM375	375 (15")	45	1280	1	
001-19-SM450	450 (18")	55	2150	1	



### NO. S 1-20 "HIT" ADJUSTABLE SPUD WRENCH

Die casting Aluminium Alloy Construction. A perfect tool for working in the tightest quarters to be reached by one hand. Jaws can be opened up to 2-11/16" (68mm) to reach difficult areas. Durable soft jaw pads protect work from marring. Best suited for polished, chrome plated, brass tubular and fittings against scratch damage or deform. Excellent for working on plumbing, water filters, PVC conduits and polished shafts.

Item No.	Length	Capacity	Wt	Packing	Price
	(mm)	(mm)	(g)	(pcs/box)	(pc)
001-20-AOM68	200	16 - 68	240	6	