



SmartBright LED Floodlight

BVP172 LED43/CW 50W WB GREY CE

SmartBright LED Floodlight, 4300 lm, 50 W, 757 cool white, Safety class I

The SmartBright LED Floodlight is a versatile floodlight engineered to deliver significant energy savings, an ideal solution for diverse floodlighting applications. The product is also designed to meet relevant performance and safety standards, offering you reliable and long-lasting performance.

Product data

| General Information | | Power Consumption | |
|------------------------------------|---|---------------------------|--------------------------|
| Driver included | No | Power Consumption | 50 W |
| Lighting Technology | LED | Power Factor (Fraction) | 0.95 |
| Flammability mark | For mounting on normally flammable surfaces | Connection | Flying leads/wires |
| CE mark | CE mark | Cable | Cable 0.6 m without plug |
| Light Technical | | Temperature | |
| Luminous Flux | 4,300 lm | Ambient temperature range | -40 to +45 °C |
| Correlated Color Temperature (Nom) | 5700 K | Controls and Dimming | |
| Luminous Efficacy (rated) (Nom) | 95 lm/W | Dimmable | No |
| Color rendering index (CRI) | >80 | Control interface | - |
| Light source color | 757 cool white | Mechanical and Housing | |
| Optical cover type | Polycarbonate bowl/cover | Housing Material | Aluminum die cast |
| Operating and Electrical | | Optical cover material | Polycarbonate |
| Input Voltage | 220 to 240 V | Housing Color | Dark gray |
| Line Frequency | 50 or 60 Hz | Overall length | 270 mm |

SmartBright LED Floodlight

| | |
|-------------------------------------|----------------------|
| Overall width | 202 mm |
| Overall height | 38 mm |
| Effective projected area | 0.054 m ² |
| Dimensions (Height x Width x Depth) | 38 x 202 x 270 mm |

Approval and Application

| | |
|------------------------------|--|
| Ingress protection code | IP65 [Dust penetration-protected, jet-proof] |
| Mech. impact protection code | IK07 [2 J reinforced] |
| Protection class IEC | Safety class I |

Initial Performance (IEC Compliant)

| | |
|-----------------------------|---------------------|
| Luminous flux tolerance | +/-10% |
| Initial chromaticity | (0.33, 0.34) SDCM<7 |
| Power consumption tolerance | +/-10% |

Product Data

| | |
|---------------------------------|--------------------------------|
| Order product name | BVP172 LED43/CW 50W WB GREY CE |
| Full product name | BVP172 LED43/CW 50W WB GREY CE |
| Full product code | 871951454868899 |
| Order code | 911401693507 |
| Material Nr. (12NC) | 911401693507 |
| Numerator - Quantity Per Pack | 1 |
| EAN/UPC - Product/Case | 8719514548688 |
| Numerator - Packs per outer box | 8 |
| EAN/UPC - Case | 8719514548800 |

Dimensional drawing

