



Datasheet

CCTV Power Supply

12Vdc IP66 Rated Range

ENGLISH



Features

- Universal AC Input
- IP Rated Weatherproof Unit
- Tightenable Glands for IP & OP Wires
- Over Voltage, Short Circuit & Over Temp. Protections
- ErP Level V
- RoHS Compliant
- MTBF >50,000 hours

RS Stock Number	Manufacturers P/N	Output Voltage	Output Current (Min)	Output Current (Max)	Power (VA)	Line Regulation	Voltage Tolerance	Ripple & Noise (mV- p-p)
8280122	T4467AD	12Vdc	0A	1A	12W	+/- 1%	+/- 5%	<120mV
8280131	T4211AD	12Vdc	0A	1.5A	18W	+/- 1%	+/- 5%	<120mV
8280134	T4466AD	12Vdc	0A	2A	24W	+/- 1%	+/- 5%	<120mV

Input

- Rated Input 100 - 240Vac
- Rated Input Frequency 50Hz
- Efficiency 75%
- Re-Wireable Terminal Block for L - E - N wires

Output

- Re-Wireable Terminal Block for 0Vdc & 24Vdc wires

Environmental

- Operating Temperature 0°C to 40°C
- Storage Temperature -10°C to 70°C
- Operating Humidity 20% to 80%
- Storage Humidity 10% to 90%

Casing

- Dimensions 60mm x 120mm x 80mm

