




Datasheet

Product Name:	UL1371 24AWG
Product Discription:	UL1371 24AWG
Specification No.:	
Customer's Name:	

Description					Construction					
Rated Voltage:	Voltage not specified				Conductor	Stranded Sliver plated copper				
Rated Temperature:	105 deg C,60 or 80 deg C Oil, Gasoline Resistant				Size(AWG)	24				
Reference Standard:	UL758				Construction(±0.008mm)	7/0.203				
Cross Section					Stranded Dia.(mm)Ref.	0.609				
					Insulation Material	PTFE				
					Insulation Color	ANY COLOR				
					Ave Thickness(mm)	0.15				
					Insulation Dia.(±0.05mm)	0.97				
Marking					Remark:					
No marking on the cable jacket					9034021 Red	9034030 Blue	9034043 Grey	9034052 Violet		
					9034024 Black	9034033 White	9034046 Yellow			
					9034027 Brown	9034037 Green	9034049 Orange			
Applications					Characteristics					
Internal Wiring, where not subjected to movement or mechanical damage					Test Item	Standard Value				Customer Approve Seal & Stamp Signature: Date:
					Test Material	PTFE(ROHS)				
Insulation resistance(20°C MΩ*m)	1000									
Vol. Tesr(AC.V.60S) (V)	2000									
Flammability Test	Horizontal flame									
Max.DC Resistance(20°C Ω/km)	78.4(MAX)									
Revisions										
Version	Description	Drawn by	Approved by	Date						
0	New document issue	Danniel	Jason	05/10/2015						