



Main

| | |
|---------------------------|-------------|
| Range | Mureva |
| Product or component type | Wander plug |
| Device short name | Mureva plug |
| Plug, socket category | Low voltage |
| Poles description | 2P + E |
| Network type | AC |
| Outlet standard | Industrial |

Complementary

| | |
|-------------------------------------|---|
| Plug, socket, control station shape | Straight |
| [In] rated current | 32 A |
| [Ue] rated operational voltage | 200...250 V |
| Network frequency | 50/60 Hz |
| Ground lug clockwise position | 6 h |
| Plug, socket material | Housing: self-extinguishing engineering polymer |
| Contacts material | Sleeves: brass |
| Connections - terminals | Captive screws |
| Cable cross section | 2.5...10 mm ² |
| Cable outer diameter | 11.5...21 mm |
| Cable entry | Fair lead Cable gland |
| Thread type | Pg 21 |
| Net weight | 0.2 kg |
| Height | 152 mm |
| Width | 76 mm |
| Depth | 76 mm |
| Colour | Grey (RAL 7035) |
| Voltage colour | Blue |

Environment

| | |
|---------------------------------------|---|
| Standards | IEC 60309-2 IEC 60309-1 |
| IP degree of protection | IP44 conforming to IEC 60529 |
| IK degree of protection | IK08 conforming to EN 62262 |
| Fire resistance | 850 °C conforming to IEC 60695-2-11 |
| Relative humidity | 50 % at 40 °C 70 % at 30 °C 90 % at 20 °C |
| Operating altitude | 2000 m |
| Ambient air temperature for operation | 35 °C (86400 s) -25...40 °C |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 5.5 cm |
| Package 1 Width | 6.2 cm |
| Package 1 Length | 16.0 cm |
| Package 1 Weight | 205.0 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 12.0 cm |
| Package 2 Width | 26.1 cm |
| Package 2 Length | 26.7 cm |
| Package 2 Weight | 2.2 kg |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 30 |
| Package 3 Height | 30.0 cm |
| Package 3 Width | 30.0 cm |
| Package 3 Length | 40.0 cm |
| Package 3 Weight | 7.1 kg |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|