

FEATURES

- Robust design with aluminium carrier
- Easy to assemble
- The strip can be cut to size using hacksaw or bolt cutters
- Resistant to most common solvents

RS PRO Aluminium, Nylon Black Brush Strip, 60mm x 13.2 mm x 12mm

RS Stock No.: 326-9959



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

From RS Pro a high-quality brush strip or brush seal which is a type of draught excluder designed to seal the gap between the bottom of a door and the floor to prevent draughts and keep in heat. As well as draught proofing, this brush strip also helps prevent dust and debris like leaves and litter from entering the threshold of a building or factory from outside. The brush strip consists of an aluminium carrier with a 180° mounting angle containing a brush made up of a row of black nylon bristles. The strip can be cut to size to provide an accurate fit to any door

Options available for RS PRO Aluminium Nylon Black Brush Strip:

- [326-9808](#) - 90 degree 19 mm x 6.7 mm x 6.7 mm
- [326-9842](#) - 90 degree 25 mm x 7.9 mm x 7.6 mm
- [326-9870](#) - 90 degree 32 mm x 7.9 mm x 7.6 mm
- [326-9886](#) - 45 degree 32 mm x 6.7 mm x 6.5 mm
- [326-9892](#) - 90 degree 45 mm x 7.9 mm x 7.6 mm
- [326-9915](#) - 90 degree 50 mm x 7.9 mm x 7.6 mm
- [326-9943](#) - 90 degree 60 mm x 13 mm x 12 mm
- [326-9959](#) - 45 degree 60 mm x 13.2 mm x 12 mm
- [326-9971](#) - 90 degree 75 mm x 13 mm x 12 mm
- [326-9993](#) - 90 degree 115 mm x 13 mm x 12 mm

General Specifications

Product Type	Strip Brush
Material	Aluminium, Nylon
Colour	Black
Applications	Bottom of revolving doors, Roller shutters, Loading bay doors, Gates and fences, Household doors, Garage doors, Sheds, Kennel doors

Mechanical Specifications

Dimensions	60mmx 12.1mm x 13.2mm
Length	60mm
Width	12.1mm
Height	13.2mm
Mounting angle	180°
Ozone resistance	NO

Operation Environment Specifications

Operating Temperature Range	-50°C to 100°C
------------------------------------	----------------



Dimensions (mm):

- Angle: 45°
- F: 25
- H: 13.2
- T: 1.6
- W: 12
- Filament Diameter: 0.4
- Bristle Length: 60

